

您設計產品時的好朋友！



Forum: [程式軟體與開發工具](#)

Topic: [MCC 產生之 I2C Slave 範例 code 請益](#)

Subject: [Re: MCC 產生之 I2C Slave 範例 code 請益](#)

作者: sarsgg444

2018年06月01日 15:14:37

剛剛修改了一下 Code

在 mcc 產生的 i2c2.c 內的 switch case 中

將 case S_SLAVE_TRANSMIT_MODE: 的最後一段加上清除 I2C2bits.I2COV 的動作後

I2C 程式就能正常讀寫了

```
case S_SLAVE_TRANSMIT_MODE:

    // this is the state where an ACK or NACK is expected
    // to occur after the slave has placed data to the
    // transmit register.

    // if the transaction was ACK'ed, more data needs to be sent
    // if the transaction was NACK'ed then we don't need to send
    // more data
    if (I2C2_ACKNOWLEDGE_STATUS_BIT == 0)
    {
        // prepare next data
        I2C2_StatusCallback(I2C2_SLAVE_TRANSMIT_REQUEST_DETECTED);

        // transmit more data
        I2C2_TransmitProcess();
    }
    else //if (I2C2_ACKNOWLEDGE_STATUS_BIT == 1)
    {
        // no more data to be sent so we go to idle state
        i2c2_slave_state = S_SLAVE_IDLE;
    }

    if( I2C2_RECEIVE_OVERFLOW_STATUS_BIT == true )
    {
        dummy = I2C2_RECEIVE_REG;
        I2C2_RECEIVE_OVERFLOW_STATUS_CLR;
    }

    break;
```

不確定是什麼原因

在 Master 向 Slave 發起 read 請求後

RBF, I2COV 被設為 1, 且直到 Read 結束後沒有被清除

導致後續 Master 發出 ADDRESS 請求, 也不會收到 Slave 端的 ACK

目前翻 datasheet 也只翻到 RBF, I2COV 被設為 1 的原因

Overrun is indicated if either (or both):

•The buffer full bit, RBF (I2CxSTAT<1>), was set before the transfer was received

•The overflow bit, I2COV (I2CxSTAT<6>), was set before the transfer was received