

104 DSP

16-bit
DSP Engine and DSP Libraries

© 2006 Microchip Technology Incorporated. All Rights Reserved. Slide 1

Class Objective

- **When you finish this class you will:**
 - Be familiar with dsPIC DSP features
 - Be familiar with using dsPIC DSP library and tools

© 2006 Microchip Technology Incorporated. All Rights Reserved. 104 DSP Slide 2




Agenda

- **Why DSP**
- **dsPIC Support for DSP**
 - dsPIC DSP architecture
 - dsPIC DSP Tools and Libraries






DSP Systems



Analysis (Receiver / Encoder)




Synthesis (Transmitter / Decoder)



Signal Conditioning/Control



Analog Control Systems



- Drawbacks:


- Low noise immunity
- Little flexibility
- Requires adjustments
- Critical component specification, especially for high order filters

- Filter characteristics change with

- Temperature
- Component aging
- Power supply variation



Digital Control Systems



- Some key advantages of digital filtering:
 - Less affected by noise
 - Lower power consumption
 - Programmable systems
 - Minimal effect of drift in characteristics with age



FIR Filters: Definition

- The input-output relation of a FIR filter is given by

$$y[n] = \sum_{k=0}^{T-1} b_k x[n-k]$$

where:


T = filter length (# of taps)

b_k = the k^{th} coefficient of the filter



FIR Filters: Structure

- **FIR filter tapped delay line form**
 - z^{-1} refers to a unit sample delay



© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP

Slide 9

HANDS-ON Training

DSP Architecture

Magnitude (dB)

Frequency (Hz)

MICROCHIP TECHNOLOGY

EXPLORE DESIGN

APPLY TRAINING CENTERS

© 2006 Microchip Technology Incorporated. All Rights Reserved.

Slide 10



dsPIC support for Filters

- DSP Library Support
- Dual Harvard Architecture
- MAC instructions with data prefetch
- Modulo Addressing
- Loop control - DO and REPEAT instructions



C-callable fixed point FIR from MPLAB

Description: FIR applies an FIR filter to the sequence of source samples, places the results in the sequence of destination samples, and updates the delay values.

Include: `dsp.h`

Prototype:

```
extern fractional* FIR (  
    int numSamps,  
    fractional* dstSamps,  
    fractional* srcSamps,  
    FIRStruct* filter  
);
```


Arguments:

<i>numSamps</i>	number of input samples to filter (also N)
<i>dstSamps</i>	pointer to destination samples (also y)
<i>srcSamps</i>	pointer to source samples (also x)
<i>filter</i>	pointer to FIRStruct filter structure


Return Value: Pointer to base address of destination samples.



dsPIC vs. Microprocessor Architectures



Dual Harvard Architecture



Von Neuman Architecture



MAC and dual parallel reads

MAC

Multiply and Accumulate

Syntax: {label;} MAC Wm*Wn, Acc {[Wx], Wxd} {[Wy], Wyd} {AWB}

Operation:

$$(\text{Acc}(A \text{ or } B)) + (Wm) * (Wn) \rightarrow \text{Acc}(A \text{ or } B)$$

$$([Wx]) \rightarrow Wxd; (Wx) + kx \rightarrow Wx$$

$$([Wy]) \rightarrow Wyd; (Wy) + ky \rightarrow Wy$$

$$(\text{Acc}(B \text{ or } A)) \text{ rounded} \rightarrow \text{AWB}$$

Description: Multiply the contents of two working registers, optionally prefetch operands in preparation for another MAC type instruction and optionally store the unspecified accumulator results. The 32-bit result of the signed multiply is sign-extended to 40 bits and added to the specified accumulator.

Words: **1** → One clock cycle, One program word!

Cycles: 1

Example 1: MAC W4*W5, A, [W8]+=6, W4, [W10]+=2, W5



Modulo: FIR Filter Example

- Single Sample FIR Filter Operation (4 taps)
- Vector Dot Product of...
 - Input Delay Line
 - Coefficient Array

$$\begin{array}{|c|c|c|c|} \hline x[n] & x[n-1] & x[n-2] & x[n-3] \\ \hline \end{array} \times \begin{array}{|c|} \hline b_0 \\ \hline b_1 \\ \hline b_2 \\ \hline b_3 \\ \hline \end{array} = \boxed{y[n]}$$

Delay line

© 2006 Microchip Technology Incorporated. All Rights Reserved.



104 DSP

Slide 17



Modulo: FIR Filter Example

Buffer at $n = 3$ (before computation):



© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP


Slide 18



Modulo: FIR Filter Example

FIR output for $n = 3$:

$$y[3] = x[3]*b_0 + x[2]*b_1 + x[1]*b_2 + x[0]*b_3$$





© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP

Slide 19



Modulo: FIR Filter Example



© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP


Slide 20



Modulo: FIR Filter Example

FIR output for $n = 4$:

$$y[4] = x[4]*b_0 + x[3]*b_1 + x[2]*b_2 + x[1]*b_3$$



© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP

Slide 21



Zero Overhead Looping

- Two Instructions
 - **REPEAT** for single instruction loops
 - **DO** for multiple instruction loops
- Interruptable
- STATUS register indicates when looping is active

© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP

Slide 22



REPEAT Examples

- REPEAT #200
MOV [W0--], [W1]++
- REPEAT W8
CLR [W5]++
- REPEAT #0x20
ADD A, [W3++]



Nested DO Example

```
DO      LOOP1, #0x100
MOV     [W0], W1
AND     #0x3FF, W1
DO      LOOP2, #0x8
BTG     W1, #0x9
LOOP2:  IOR     W1, [W2]++, [W3]++
LOOP1:  MOV     W1, [W0]++
```



4 Lines (dsPIC) vs. 31 Lines (16-bit MCU)

```

repeat   w4
mac      w5*w6,a,[w8]+=2,w5,[w10]+=2,w6
mac      w5*w6,a,[w8]+=2,w5,[w10],w6
mac      w5*w6,a

```

16-bit MCU

```

do_again1:
mov      R6,[R5]    ;Get next x(n-1)
mov      R7,[R12+]  ;Get next FIR filter coeff-a(i)
mul      R6,R7      ;Form product a(i)*x(n-1)
jmp      cc_NV,copy1 ;Test for only 16 bit result
mov      R9,MDH     ;Move high portion of MD

copy1:
mov      R6,MDL     ;Move low portion of MD
add      R11,R6     ;acc. Product terms in R10 and R11
addc    R10,R9
sub      R5,#2      ;Point to a next item in x(n-1)
cmp      R5,R13     ;Chk if ptr falls out of circ buffer table
jmp      cc_NN,leap1 ;if still in table keep going otherwise
                                ;adj. Ptr. To top of table

mov      R4,R2
shl      R4,#1
add      R5,R4      ;adj. Ptr to top of table

leap1:
add      R1,#1h     ;Determine if all taps computed
cmp      R1,R2
jmp      cc_NZ,do_again1
mov      R4,#curr_ptr
mov      R5,[R4]
add      R5,#2h     ;Inc. ptr. Into circ. Buffer
mov      R3,R2
shl      R3,#1
sub      R3,#2
mov      R6,R13
add      R6,R3
cmp      R5,R6      ;Does curr_ptr exceed top of table?
jmp      cc_NZ,leap3
mov      R5,R13     ;Back to beginning of table

leap3:
cmp      R10,#0h
jmp      cc_Z,leap2


```



DSP Benchmark

● BDTI's Real Block FIR Filter Benchmark

— Execution time (lower is better)






dsPIC[®] Digital Filter Design

- **Graphically design all types of digital filters**
 - Low-pass, high-pass
 - Band-pass, band-stop
- **Digital filter algorithm kernels are provided for:**
 - FIR—Finite Impulse Response
 - IIR—Infinite Impulse Response
- **Designing coefficients to control the filter response is the tricky part**
 - You can do the math or use this tool!!
- **Quickly observe filters response**
- **Generated code and coefficients fully compatible with MPLAB[®] C30 C Compiler language tools**

© 2006 Microchip Technology Incorporated. All Rights Reserved. 104 DSP Slide 28



dsPIC[®] Digital Filter Design



© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP

Slide 29



dsPICWorks[™] Data Analysis and DSP Software

- Graphical signal analysis and generation tool
 - Create waveforms and process them
 - Signal generation
 - SIN, square, swept SIN, triangular, etc...
 - Signal operations
 - Add, Flip and Shift, Multiply, etc...
 - DSP operations
 - Filtering, correlation, FFT, LPC analysis, etc...
- Designed especially for the dsPIC30F
 - Import/export data with MPLAB[®] compatible files
 - Processes filter files saved from dsPIC[®] Digital Filter Design


© 2006 Microchip Technology Incorporated. All Rights Reserved.

104 DSP

Slide 30



dsPICWorks™ Data Analysis



HANDS-ON
Training

Lab 1

Using DSP Tools and Libraries

MICROCHIP TECHNOLOGY
EXPLORE DESIGN
APPLY TRAINING CENTERS

© 2006 Microchip Technology Incorporated. All Rights Reserved.

Slide 32



Lab 1 – Using DSP

- **Goals**

- Learn DSP tools and Libraries

- **Lab**

- Implement signal filtering using FIR filter

HANDS-ON Training

DSP Related Libraries

MICROCHIP TECHNOLOGY
EXPLORE DESIGN
APPLY TRAINING CENTERS

© 2006 Microchip Technology Incorporated. All Rights Reserved.

Slide 34



Math Library

- **Supports all of <MATH.H> from ANSI “C”**
 - Trigonometric Functions
 - Exponent and Log Functions
 - Power, Square Root, Floor, Ceiling, etc.
- **IEEE-754 Compliant**
- **Optimized for code size, developed in Assembly**
- **Supports 2 data types**
 - 32-bit floating point
 - 64-bit double
- **Benefits any application which uses floats/doubles**
- **C and assembly callable**



DSP Library

- **Libraries for your DSP requirements**
- **Collection of 49 of the most common DSP functions**
 - Vector and Matrix Functions
 - **Add, Subtract, Multiply, Max, Min**
 - **Convolution, Correlation, Power, etc...**
 - Filter Functions—block and single sample processing
 - **FIR, IIR, Adaptive LMS, Lattice and more**
 - Transform Functions
 - **FFT, Inverse FFT, Discrete Cosine Transform**
 - Window Functions
 - **Bartlett, Blackman, Hamming, Hanning, Kaiser**
- **Most functions are hand coded in assembly language**
 - Fast execution time, C and assembly callable



Embedded Modem Library

- **Software Modem (soft-modem) Support**
 - Replacing external modem chip with software!
- **Benefits**
 - Single-chip integrated solution (up to 14.4 kbps)
 - Quick dialup and connection times
 - **Perfect for small transactions on analog phone line**
- **Application Examples**
 - Home automation, remote access, security systems
 - POS applications, web-enabled devices
 - Tele-metering, remote upgrades
- **Library supplied with full DTMF Generation/Detection modules**



Soft-Modem Resource Summary

- **dsPIC30F implementation leaves room for other tasks...**



ITU-T Specification	Bit Rate (bps)	RAM (Bytes)	Program Memory (Kbytes)	MIPS
V.32bis	14400	3600	36	15
V.32	9600	3200	31	12
V.22bis	2400	1700	22	7
V.23	600/1200	1000	15	4.5
V.21	300	1000	13	4.5
V.42 (Error Corr.)	na	2000	14	1.5

Includes DTMF Library



Speech Coding Library

- **Performs speech compression / decompression**
- **Encoder - 16:1 compression ratio**
 - Speech input: 8 KHz, 16-bit mono
 - Encoded output: 8kbps data stream
- **Decoder**
 - Decoder input: 8 kbps data stream
 - Speech output: 8 KHz, 16-bit mono
- **Based on Speex**
 - Open source technology
 - Numerous PC plug-ins / apps readily available
 - www.speex.org
- **Includes PC Utility for making “playback” files**



Speech Coding Library How may it be used?

- **By any application with voice communication**
- **Benefits**
 - Reduces communication bandwidth
 - Reduces storage requirements
- **Sample Applications**
 - Digital radios / walkie-talkies
 - Answering machines / voice recorders
 - Playback-only systems
 - **Security Systems (building evacuation)**
 - **Museum Guides**
 - **Application Voice Prompts**



Speech Coding Library Resource Requirements

- Small Decoder footprint / Encoder is RAM intensive


	Encoder	Decoder
MIPs	19	3
RAM	5.4 KB	3.2 KB
Flash	33 KB	15 KB

- 2 analog interfaces supported
 - Silicon Labs Si-3000 Codec
 - Alternate interface for cost-sensitive applications
 - ADC for microphone input
 - Output compare for speaker output
 - Sample circuits provided in User's Guide



Acoustic Echo Cancellation Library

- Provides 'far-end' echo cancellation
 - Speaker output is picked up by the local microphone and transmitted back to the sender
- Features
 - G.167-compliant algorithm (up to 64 msec)
 - Supports full-duplex operation





Acoustic Echo Cancellation Library

- **G.167 CPU Resources**

Echo Delay	RAM (KB)	Program Memory (KB)	MIPS
16 msec	4.6*	6	7.5
32 msec	5.4*	6	10.5
64 msec	7.7*	6	16.5

* Includes up to 2KB for CODEC and UART buffers and A/U-law compression

- **Target Applications**


- Speakerphone
- Hands-free car phone
- Intercom
- Emergency alarm units



Noise Suppression Library

- **Removes extraneous noise picked up by microphone**

- Voice activity detector differentiates noise and speech
- Noise reduction filters adjust every 10 ms during periods of speech inactivity (uses FFT analysis)
- Speech is continuously filtered, reducing noise





Noise Suppression Library

- **Noise Suppression CPU Resources**
 - 3.3 MIPS
 - 5 Kbytes Flash memory
 - 2 Kbytes RAM
 - Includes up to 1 Kbyte for buffering Codec data
- **Target Applications**
 - Front end for any voice based system
 - Headsets
 - Hands-free telephone
 - Intercom
 - Speech recognition
 - Speech coding



Embedded Encryption Libraries

- **dsPIC30F Symmetric Key Library**
 - Message Digests: SHA-1, MD5
 - Symmetric Key Encryption: T-DES, AES
 - Deterministic Random Bit Generator: ANSI X9.82
- **dsPIC30F Asymmetric Key Library**
 - Signing and Verification: RSA, DSA
 - Public Key Encryption: RSA
 - Key Agreement Protocol: Diffie-Hellman
 - Big Integer Arithmetic Package



Embedded Encryption Applications

- **Secure Web Transactions**
 - Secure web access (SSL/TLS)
 - E-mail (S/MIME), secure XML transactions, and Virtual Private Networks (IPsec)
- **Smart Card Readers**
- **PDA's and other mobile devices**
- **Secure communications between a dsPIC® DSC application and personal computers**
 - Trusted Computing Group (TCG)
 - Microsoft® Next Generation Secure Computing Base (NGSCB)



Summary

- We learned advantages of dsPIC DSP architecture
- We learned DSP tools and libraries available for dsPIC



References

- dsPIC30 & dsPIC33 Datasheet
- dsPICDEM1.1 User's Guide
- MPLAB[®] IDE
- C30 Compiler
- ICD2 In Circuit Debugger

HANDS-ON Training

All Done!
Thank you all for attending
Please remember the evaluation sheets

MICROCHIP TECHNOLOGY
EXPLORE DESIGN
APPLY TRAINING CENTERS

© 2006 Microchip Technology Incorporated. All Rights Reserved.

Slide 50



Trademarks

The Microchip name and logo, the Microchip logo, Accuron, dsPIC, KeeLoq, microID, MPLAB, PIC, PICmicro, PICSTART, PRO MATE, PowerSmart, rfPIC and SmartShunt are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AmpLab, FilterLab, Migratable Memory, MXDEV, MXLAB, SEEVAL, SmartSensor and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Analog-for-the-Digital Age, Application Maestro, dsPICDEM, dsPICDEM.net, dsPICworks, ECAN, ECONOMONITOR, FanSense, FlexROM, fuzzyLAB, In-Circuit Serial Programming, ICSP, ICEPIC, Linear Active Thermistor, Mindi, MiWi, MPASM, MPLIB, MPLINK, MPSIM, PICkit, PICDEM, PICDEM.net, PICLAB, PICtail, PowerCal, PowerInfo, PowerMate, PowerTool, REAL ICE, rfLAB, rfPICDEM, Select Mode, Smart Serial, SmartTel, Total Endurance, UNI/O, WiperLock and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

All other trademarks mentioned herein are property of their respective companies.