



MICROCHIP

Instruction Set *(x14)*




PICmicro[®] MCU Instruction Set

- 12-bit core → 33 instructions
 - 14-bit core → 35 instructions
 - 16-bit core → 58 instructions
 - 16-bit enh. core → 77 instructions
-
- Easy to learn
 - High compaction
 - Very powerful single-word instructions
 - All single- cycle except program branches
 - Upward compatibility of instructions



PIC16CXX Architecture Clocking Scheme

- Instruction cycle rate is 1/4 of clock input frequency
- Instruction cycle is 200 ns at 20 MHz clock rate



Legend: Typically: Q1 = Read Q2 = Decode Q3 = Execute Q4 = Write

PICmicro MCU Instruction Set Summary (14-bit core)

Byte-Oriented Operations

NOP	-	No Operation
MOVWF	f	Move W to f
CLRW	-	Clear W
CLRF	f	Clear f
SUBWF	f,d	Subtract W from f
DECF	f,d	Decrement f
IORWF	f,d	Inclusive OR W and f
ANDWF	f,d	AND W and f
XORWF	f,d	Exclusive OR W and f
ADDWF	f,d	Add W and f
MOVF	f,d	Move f
COMF	f,d	Complement f
INCF	f,d	Increment f
DECFSZ	f,d	Decrement f, skip if zero
RRF	f,d	Rotate right f through carry
RLF	f,d	Rotate left f through carry
SWAPF	f,d	Swap nibbles of f
INCFSZ	f,d	Increment f, skip if zero

Bit-Oriented Operations

BCF	f,b	Bit clear f
BSF	f,b	Bit set f
BTFSC	f,b	Bit test f, skip if clear
BTFSS	f,b	Bit test f, skip if set

Literal and Control Operations

SLEEP	-	Go into standby mode
CLRWDT	-	Clear watchdog timer
RETLW	k	Return, place literal in W
RETFIE	-	Return from interrupt
RETURN	-	Return from subroutine
CALL	k	Call subroutine
GOTO	k	Go to address (k is 9-bit)
MOVLW	k	Move literal to W
IORLW	k	Inclusive OR literal with W
ADDLW	k	Add literal with W
SUBLW	k	Subtract W from literal
ANDLW	k	AND literal with W
XORLW	k	Exclusive OR literal with W

f = File Register, k = literal value (8-bit), b = bit address <0,7>, d = destination (0=f, 1=W)



PICmicro MCU Instruction Set

Byte-Oriented Operations

Byte-Oriented Operations

NOP	-
MOVWF	f
CLRW	-
CLRF	f
SUBWF	f,d
DECF	f,d
IORWF	f,d
ANDWF	f,d
XORWF	f,d
ADDWF	f,d
MOVF	f,d
COMF	f,d
INCF	f,d
DECFSZ	f,d
RRF	f,d
RRL	f,d
SWAPF	f,d
INCFSZ	f,d

14-bit Instruction for Byte Oriented Operations



d = Destination Bit

d = 0 for destination W
d = 1 for destination F

f = 7-bit Register Address

Example:

ADDWF REG, W

ADDWF f, d



PICmicro MCU Instruction Set

Byte-Oriented Operations

NOP **No Operation**

Syntax: **NOP**

Operands: **None**

Operation: **No operation**

Status: **None**

Encoding: **00 0000 0000 0000**

Words: **1**

Cycles: **1**

- Example:
NOP



PICmicro MCU Instruction Set

Byte-Oriented Operations

MOVWF **Move W to f**

Syntax: MOVWF f

Operands: $0 \leq f \leq 127$

Operation: (W) \rightarrow (f)

Status: None

Encoding: 00 0000 1fff fff

Words: 1

Cycles: 1

- Example:

MOVWF FSR

Before Instruction

FSR = 0xFF

W = 0x4F

After Instruction

FSR = 0x4F

W = 0x4F



PICmicro MCU Instruction Set

Byte-Oriented Operations

CLRW **Clear W**

Syntax: CLRW

Operands: None

Operation: 00h -> (W)

1 -> Z

Status: Z

Encoding: 00 0001 0000 0000

Words: 1

Cycles: 1

- Example:

CLRW

Before Instruction

W = 0x4F

After Instruction

W = 0x00

Z = 1



PICmicro MCU Instruction Set

Byte-Oriented Operations

CLRF

Clear f

Syntax: CLRF f

Operands: $0 \leq f \leq 127$

Operation: 00h \rightarrow (f)

1 \rightarrow Z

Status: Z

Encoding: 00 0001 1fff ffff

Words: 1

Cycles: 1

- Example:

CLRF FSR

Before Instruction

FSR = 0x4F

After Instruction

FSR = 0x00

Z = 1



PICmicro MCU Instruction Set

Byte-Oriented Operations

SUBWF Subtract W from f

Syntax: SUBWF f,d

Operands: $0 \leq f \leq 127$

$d = \{0,1\}$

Operation: $(f) - (W) \rightarrow \text{dest}$

Status: C,DC,Z

Encoding: 00 0010 dfff ffff

Words: 1

Cycles: 1

● Example:

SUBWF FSR,0

Before Instruction

FSR = 0x03

W = 0x02

C = ?

Z = ?

After Instruction

FSR = 0x03

W = 0x01

C = 1

Z = 0



PICmicro MCU Instruction Set

Byte-Oriented Operations

DECF **Decrement f**

Syntax: `DECF f,d`

Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$

Operation: $(f) - 1 \rightarrow \text{dest}$

Status: **Z**

Encoding: `00 0011 dfff ffff`

Words: 1

Cycles: 1

- Example:
DECF FSR,1
- Before Instruction
- | | |
|-----|--------|
| FSR | = 0x01 |
| Z | = 0 |
- After Instruction
- | | |
|-----|--------|
| FSR | = 0x00 |
| Z | = 1 |



PICmicro MCU Instruction Set

Byte-Oriented Operations

IORWF Inclusive OR W & f

Syntax: IORWF f,d

Operands: $0 \leq f \leq 127$

$d = \{0,1\}$

Operation: (W) .OR. (f) -> dest

Status: Z

Encoding: 00 0100 dfff ffff

Words: 1

Cycles: 1

● Example:

IORWF CNT,0

Before Instruction

CNT = 0x13

W = 0x91

After Instruction

CNT = 0x13

W = 0x93

Z = 0



PICmicro MCU Instruction Set

Byte-Oriented Operations

ANDWF **AND W with f**
Syntax: ANDWF f,d
Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$
Operation: $(W).AND.(f) \rightarrow dest$
Status: Z
Encoding: 00 0101 dfff ffff
Words: 1
Cycles: 1

- Example:
ANDWF CNT,1
Before Instruction
CNT = 0x17
W = 0xC2

After Instruction
CNT = 0x02
W = 0xC2
Z = 0



PICmicro MCU Instruction Set

Byte-Oriented Operations

XORWF Exclusive OR W & f

Syntax: XORWF f,d

Operands: $0 \leq f \leq 127$

$d = \{0,1\}$

Operation: $(W).XOR.(f) \rightarrow \text{dest}$

Status: Z

Encoding: 00 0110 dfff ffff

Words: 1

Cycles: 1

● Example:

XORWF FSR,0

Before Instruction

FSR = 0xAF

W = 0xB5

After Instruction

FSR = 0xAF

W = 0x1A

Z = 0



PICmicro MCU Instruction Set

Byte-Oriented Operations

ADDWF *Add W with f*

Syntax: `ADDWF f,d`

Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$

Operation: $(W) + (f) \rightarrow \text{dest}$

Status: `Z`

Encoding: `00 0111 dfff ffff`

Words: `1`

Cycles: `1`

- Example:
ADDWF FSR,0
- Before Instruction
- | | |
|-----|--------|
| FSR | = 0x17 |
| W | = 0xC2 |
- After Instruction
- | | |
|-----|--------|
| FSR | = 0x17 |
| W | = 0xD9 |
| Z | = 0 |



PICmicro MCU Instruction Set

Byte-Oriented Operations

MOVF **Move f**

Syntax: MOVF f,d

Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$

Operation: (f) -> dest

Status: Z

Encoding: 00 1000 dfff ffff

Words: 1

Cycles: 1

- Example:
MOVF FSR,1
- Before Instruction
- | | |
|-----|--------|
| FSR | = 0x00 |
| Z | = 0 |
- After Instruction
- | | |
|-----|--------|
| FSR | = 0x00 |
| Z | = 1 |



PICmicro MCU Instruction Set

Byte-Oriented Operations

COMF **Complement f**

Syntax: MOVF f,d

Operands: $0 \leq f \leq 127$

$d = \{0,1\}$

Operation: $\overline{(f)} \rightarrow \text{dest}$

Status: Z

Encoding: 00 1001 dfff ffff

Words: 1

Cycles: 1

- Example:

COMF REG,0

Before Instruction

REG = 0x13

W = 0x58

Z = 0

After Instruction

REG = 0x13

W = 0xEC

Z = 0



PICmicro MCU Instruction Set

Byte-Oriented Operations

INCF **Increment f**

Syntax: INCF f,d

Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$

Operation: $(f) + 1 \rightarrow \text{dest}$

Status: Z

Encoding: 00 1010 dfff ffff

Words: 1

Cycles: 1

- Example:
INCF REG,1
- Before Instruction
- | | |
|-----|--------|
| REG | = 0xFF |
| Z | = 0 |
- After Instruction
- | | |
|-----|--------|
| FSR | = 0x00 |
| Z | = 1 |



PICmicro MCU Instruction Set

Byte-Oriented Operations

DECFSZ **Dec. f, Skip if 0**

Syntax: `DECFSZ f,d`

Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$

Operation: $(f) - 1 \rightarrow \text{dest}$
 skip if result = 0

Status: None

Encoding: `00 1011 dfff ffff`

Words: 1

Cycles: 1(2)

Example:

```
Loop DECFSZ CNT,1  
          GOTO Loop  
Continue
```

Before Instruction

PC = address *Loop*

After Instruction

CNT = CNT - 1

if CNT = 0,

PC = address *Continue*

if CNT \neq 0,

PC = address *Loop+1*



PICmicro MCU Instruction Set

Byte-Oriented Operations

RRF Rotate Right $f \rightarrow C$

Syntax: RRF f,d

Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$

Operation:



Status: C

Encoding: 00 1100 dfff ffff

Words: 1

Cycles: 1

Example:

RRF *CNT,0*

Before Instruction

CNT = 1110 0110

C = 0

After Instruction

CNT = 1110 0110

W = 0111 0011

C = 0



PICmicro MCU Instruction Set

Byte-Oriented Operations

RLF Rotate Left $f \rightarrow C$

Syntax: RLF f,d

Operands: $0 \leq f \leq 127$
 $d = \{0,1\}$

Operation:



Status: C

Encoding: 00 1101 dfff ffff

Words: 1

Cycles: 1

Example:

RLF *CNT,0*

Before Instruction

CNT = 1110 0110

C = 0

After Instruction

CNT = 1110 0110

W = 1100 1100

C = 1



PICmicro MCU Instruction Set

Byte-Oriented Operations

SWAPF **Swap Nibbles in f**

Syntax: SWAPF f,d

Operands: $0 \leq f \leq 127$

$d = \{0,1\}$

Operation: $f\langle 3:0 \rangle \rightarrow \text{dest}\langle 7:4 \rangle$

$f\langle 7:4 \rangle \rightarrow \text{dest}\langle 3:0 \rangle$

Status: None

Encoding: 00 1110 dfff ffff

Words: 1

Cycles: 1

Example:

SWAPF REG,0

Before Instruction

REG = 0xA5

After Instruction

REG = 0xA5

W = 0x5A



PICmicro MCU Instruction Set

Byte-Oriented Operations

INCFSZ **Inc. f, Skip if 0**

Syntax: INCFSZ f,d

Operands: 0 <= f <= 127
 d = {0,1}

Operation: (f) + 1 -> dest
 skip if result = 0

Status: None

Encoding: 00 1111 dfff ffff

Words: 1

Cycles: 1(2)

Example:

```
Loop INCFSZ CNT,1  
          GOTO Loop  
Continue
```

Before Instruction

PC = address *Loop*

After Instruction

CNT = CNT + 1

if CNT = 0,

PC = address *Continue*

if CNT != 0,

PC = address *Loop+1*



PICmicro MCU Instruction Set

Bit-Oriented Operations

Bit-Oriented Operations

BCF f,b
BSF f,b
BTFSC f,b
BTFSS f,b

14-bit Instruction for Bit Oriented Operations



b = 3-Bit Address
(Bit Number)

f = 7-bit Register Address

Example:

BTFSC **STATUS, C**
BTFSC *f, b*



PICmicro MCU Instruction Set

Bit-Oriented Operations

BCF **Bit Clear f**

Syntax: BCF f,b

Operands: $0 \leq f \leq 127$
 $0 \leq b \leq 7$

Operation: $0 \rightarrow (f \langle b \rangle)$

Status: None

Encoding: 01 00bb bfff ffff

Words: 1

Cycles: 1

- Example:
BCF FSR,4
Before Instruction
FSR = 0011 0000

After Instruction
FSR = 0010 0000



PICmicro MCU Instruction Set

Bit-Oriented Operations

BSF **Bit Set f**

Syntax: BSF f,b

Operands: $0 \leq f \leq 127$
 $0 \leq b \leq 7$

Operation: 1 -> (f)

Status: None

Encoding: 01 01bb bfff ffff

Words: 1

Cycles: 1

- Example:
BSF FSR,4
Before Instruction
FSR = 0010 0000

After Instruction
FSR = 0011 0000



PICmicro MCU Instruction Set

Bit-Oriented Operations

BTFSC **Bit Test f, Skip if 0**

Syntax: BTFSC f,b

Operands: $0 \leq f \leq 127$

$0 \leq b \leq 7$

Operation: skip if (f) = 0

Status: None

Encoding: 01 10bb bfff ffff

Words: 1

Cycles: 1(2)

Example:

Here BTFSC CNT,1

False GOTO Done

True

Before Instruction

PC = address *Here*

After Instruction

if CNT<1> = 0,

PC = address *True*

if CNT<1> = 1,

PC = address *False*



PICmicro MCU Instruction Set

Bit-Oriented Operations

BTFSS **Bit Test f, Skip if 1**

Syntax: BTFSS f,b

Operands: $0 \leq f \leq 127$

$0 \leq b \leq 7$

Operation: skip if (f) = 1

Status: None

Encoding: 01 11bb bfff ffff

Words: 1

Cycles: 1(2)

Example:

Here BTFSS CNT,1

False GOTO Done

True

Before Instruction

PC = address *Here*

After Instruction

if CNT<1> = 1,

PC = address *True*

if CNT<1> = 0,

PC = address *False*



PICmicro MCU Instruction Set


Example: Bit Manipulation

- Synchronous serial transmission of eight bits of data from file register XDATA to I/O Pin:

```

XMIT:      MOVLW      0x08      ;Bit count = 8
           MOVWF      bit_count

XM_LOOP:
           BCF        PORTB,DT  ;preset clock & data lines to 0
           BCF        PORTB,CLK  ;preset clock & data lines to 0
           RRF        XDATA,F    ;rotate data right thru Carry
           BTFSC      STATUS,C   ;test carry bit
           BSF        PORTB,DT  ;set 1 → Data pin
           BSF        PORTB,CLK  ;set 1 → Clock pin
           DECFSZ     bit_count,F ;decrement count
           GOTO       XM_LOOP    ;Not done then repeat
           BCF        PORTB,CLK  ;clear clock line and exit
    
```



PICmicro MCU Instruction Set

Literal Operations

Literal Operations

MOVLW	k
IORLW	k
ADDLW	k
SUBLW	k
ANDLW	k
XORLW	k

14-bit Instruction for Literal Operations



k = 8-bit Immediate Value

Example:

MOVLW 0x2F

MOVLW k



PICmicro MCU Instruction Set

Literal Operations

MOVLW **Move Literal to f**

Syntax: MOVLW k

Operands: 0 <= k <= 255

Operation: k -> (W)

Status: None

Encoding: 11 0000 kkkk kkkk

Words: 1

Cycles: 1

- Example:

MOVLW 0x5A

After Instruction

W = 0x5A



PICmicro MCU Instruction Set

Literal Operations

IORLW Inclusive OR Literal
with f

● Example:
IORLW 0x35

Syntax: IORLW k

Operands: $0 \leq k \leq 255$

Operation: $(W) .OR. k \rightarrow (W)$

Status: Z

Encoding: 11 1000 kkkk kkkk

Words: 1

Cycles: 1

Before Instruction

W = 0x9A

After Instruction

W = 0xBF

Z = 0



PICmicro MCU Instruction Set

Literal Operations

ADDLW Add Literal with f

Syntax: ADDLW k

Operands: $0 \leq k \leq 255$

Operation: $(W) + k \rightarrow (W)$

Status: C,DC,Z

Encoding: 11 1110 kkkk kkkk

Words: 1

Cycles: 1

- Example:
ADDLW 0x15

Before Instruction

W = 0x10

After Instruction

W = 0x25



PICmicro MCU Instruction Set

Literal Operations

SUBLW Subtract W from
Literal

Syntax: SUBLW k

Operands: $0 \leq k \leq 255$

Operation: $k - (W) \rightarrow (W)$

Status: C,DC,Z

Encoding: 11 1100 kkkk kkkk

Words: 1

Cycles: 1

- Example:
SUBLW 0x02

Before Instruction

W = 2

C = ?

Z = ?

After Instruction

W = 0x00

C = 1

Z = 1



PICmicro MCU Instruction Set

Literal Operations

ANDLW **AND Literal with f**

Syntax: `ANDLW k`

Operands: $0 \leq k \leq 255$

Operation: $(W) \text{ .AND. } k \rightarrow (W)$

Status: Z

Encoding: `11 1001 kkkk kkkk`

Words: 1

Cycles: 1

● Example:

ANDLW 0x5F

Before Instruction

W = 0xA3

After Instruction

W = 0x03



PICmicro MCU Instruction Set

Literal Operations

XORLW Exclusive OR Literal
with f

● Example:
XORLW 0xAF

Syntax: XORLW k

Operands: $0 \leq k \leq 255$

Operation: $(W) \text{ .OR. } k \rightarrow (W)$

Status: Z

Encoding: 11 1010 kkkk kkkk

Words: 1

Cycles: 1

Before Instruction

W = 0xB5

After Instruction

W = 0x1A



PICmicro MCU Instruction Set

Control Operations

Control Operations

SLEEP	-
CLRWDT	-
RETLW	k
RETFIE	-
RETURN	-
CALL	k
GOTO	k

14-bit Instruction for RETLW



k = 8-bit Immediate Value

14-bit Instruction for CALL and GOTO



k = 11-bit Immediate Value



PICmicro MCU Instruction Set

Control Operations

SLEEP Enter SLEEP mode

● Example:
SLEEP

Syntax: SLEEP

Operands: None

Operation: 00h -> WDT

 1 -> \overline{TO}

 0 -> \overline{PD}

Status: \overline{TO} , \overline{PD}

Encoding: 00 0000 0110 0011

Words: 1

Cycles: 1



PICmicro Instruction Set

Control Operations

CLRWDT	Clear Watchdog	● Example:
Syntax:	CLRWDT	<i>CLRWDT</i>
Operands:	None	
Operation:	00h -> WDT 0 -> WDT prescaler 1 -> \overline{TO} 1 -> \overline{PD}	
Status:	\overline{TO} , \overline{PD}	
Encoding:	00 0000 0110 0100	
Words:	1	
Cycles:	1	



PICmicro MCU Instruction Set

Control Operations

RETLW Return with Literal
 in f

Syntax: RETLW k

Operands: $0 \leq k \leq 255$

Operation: $k \rightarrow (W)$
 TOS \rightarrow PC

Status: None

Encoding: 11 0100 kkkk kkkk

Words: 1

Cycles: 2

● Example:
RETLW 0x5A

After Instruction
 W = 0x5A



PICmicro MCU Instruction Set

Control Operations

RETFIE Return from
Interrupt

- Example:
RETFIE

Syntax: RETFIE

Operands: None

Operation: TOS -> PC
 1 -> GIE

Status: None

Encoding: 00 0000 0000 1001

Words: 1

Cycles: 2



PICmicro MCU Instruction Set

Control Operations

RETURN Return from
Subroutine

- Example:
RETURN

Syntax: RETURN

Operands: None

Operation: TOS -> PC

Status: None

Encoding: 00 0000 0000 1000

Words: 1

Cycles: 2



PICmicro MCU Instruction Set

Control Operations

CALL **Call Subroutine**

Syntax: CALL k

Operands: $0 \leq f \leq 2047$

Operation: (PC) + 1 -> TOS
 k -> PC<10:0>
 PCLATH<4:3 ->
 PC<12:11>

Status: None

Encoding: 10 0kkk kkkk kkkk

Words: 1

Cycles: 2

Example:

Here CALL There

Before Instruction

PC = address *Here*

After Instruction

PC = address *There*

TOS = address *Here+1*



PICmicro MCU Instruction Set

Control Operations

GOTO **Unconditional
Branch**

Syntax: GOTO k

Operands: 0 <= f <= 2047

Operation: k -> PC<10:0>
 PCLATH<4:3> ->
 PC<12:11>

Status: None

Encoding: 10 1kkk kkkk kkkk

Words: 1

Cycles: 2

Example:

GOTO *There*

After Instruction

PC = address *There*



PICmicro MCU Instruction Set

Instruction Set Demo

