



MICROCHIP


Regional Training Centers

HIF2132A

**Designing Stylish HMI's with Microchip's
Graphics Library and Visual Graphics Display
Designer using PIC32 LCC Graphics**



The Board



- PSRAM for external frame buffer.
- Internal/External Memory Jumpers
- Part Number:
 - AC164144



Class Objectives

After this class you will be able to:

- **Use a PC based graphical design tool to create a customized user interface code template.**
- **Implement application callback functions to allow users to fully interact with the system**
- **Use advanced features in Microchip's Graphics Library to enhance your GUI appearance**
- **Learn about the LCC Graphics Solution**




Agenda

- **Microchip Graphics Library Intro**
- **Graphics Basics and Terminology**
 - **Colors and Images**
 - **Fonts**
 - **Widgets and Style Schemes**
- **Lab 1 – Creating a Splash Screen**
- **Lab 2 – Creating a Simple Icon Menu**
- **Interfacing the User (Message Interface)**
- **Lab 3 – User Interface using Message Callback**
- **Advanced Features (Drawing Callback)**



Agenda

- **LCC Interfacing to TFT LCD Panels**
- **PIC32 Peripherals Used for Graphics**
 - **DMA**
 - **PMP**
- **Controller/Driver Tasks**
- **Lab 4 – LCC and Primitive Layer Demo**
- **Customizing for YOUR application**
- **Summary**




Embedded Graphics Systems


Overview




How it works ...




Summary of Graphical Setups



LCC Controllerless method



- **Cost Effective**
- **Works on many platforms**



Microchip Graphics Library

Overview



MICROCHIP

Regional Training
Centers

Graphics Library




- Works with 16- and 32-bit PIC[®] MCUs
- Modular design – compile only what you need!
- Supports up to 24 bpp color depth
- Supports gradients, transparency, alpha blending, and transitions
- Demo source provided for our low-cost, full featured development tools
- Free to Microchip customers
 - Source code included
 - Multiple display controller drivers included





Library Overview





MICROCHIP

Regional Training
Centers

Graphics Design Center

<http://www.microchip.com/graphics>

myMicrochip Login | English | 中文 | 日本語

search

Home Products Design Support Applications Buy/Sample Corporate What's New

MICROCHIP

► Resources and Support

► Related Pages

► Featured Videos

► Find Products

Graphics Displays

Overview Technology Products Support Getting Started

NEWS AND EVENTS PIC24FJ DA Family with integrated Graphics

ADDING GRAPHICS TO YOUR APPLICATION

EXPLORE THE POSSIBILITIES

FREE MICROCHIP GRAPHICS LIBRARY

FREE MICROCHIP GRAPHICS LIBRARY

Download Microchip Applications Library



MICROCHIP

Regional Training
Centers

Microchip Libraries for Applications

<http://www.microchip.com/MLA>


Library	Current Version	PIC16F (8-bit)	PIC18F (8-bit)	PIC24/dsPIC (16-bit)	PIC32 (32-bit)
USB Framework	2.9e		x	x	x
Graphics Library	3.04.02			x	x
Memory Disk Drive (MDD)	1.3.8		x	x	x
TCP/IP Stack	5.41.02		x	x	x
(TCP/IP Stack v6.00 beta available for download below)	v6.00 beta			x	x
mTouch Capacitive Touch Library	1.40.02	x	x	x	x
Smart Card Library	1.02.6		x	x	x
MiWi™ Development Environment	4.2.4		x	x	x
Accessory Framework for Android™	1.01.02			x	x

Microchip Application Libraries

Downloads	Comments
Microchip Application Libraries v2012-04-03 Windows	
Microchip Application Libraries v2012-04-03 Linux	
Microchip Application Libraries v2012-04-03 Mac OS X	


Microchip Solutions Directory

- Reference Design Projects
 - Full source code
- Find individual projects in these directories
- All paths relative to the Microchip directory




Microchip Solutions Board Support

- Microchip development / evaluation board support
 - Touch screen
 - Memory
 - Potentiometer
 - Accelerometer
 - etc...




Microchip Solutions Library Source Code

- Source files for all libraries
- Help files for all libraries



Microchip Solutions Library Help Files

- [../Microchip/Help](#)
- Abbreviations for the Microchip development boards used in demos
- Graphics Library APIs and demo user guides





MICROCHIP

Regional Training
Centers

Library Help

Help files are included as part of the Microchip Graphics Library installation and are located in the following directory:


..\Microchip\Help



Graphics Library Help.chm




Graphics Library Help.pdf




Microchip Solutions Graphics Library

- `../Microchip/Graphics`
- Schematics for the Microchip Graphics development boards
- User's guides for Microchip Graphics demo projects




Microchip Solutions Graphics Library

- [../Microchip/Graphics](#)
- Free fonts
- Free images and icons



Microchip Solutions Graphics Library

- `../Microchip/Graphics`
- 'C' source files for graphics (LCD) controllers






MICROCHIP

**Regional Training
Centers**

Microchip Graphics Library

Help -> Release Notes


Display Module	Interface	File Names
Microchip Graphics Display Driver - customizable driver for RGB Glass. Currently used in PIC24FJ256DA210 device family.	RGB	mchpGfxDrv.c, mchpGfxDrv.h
Microchip Low-Cost Controllerless (LCC) Graphics Display Driver - customizable driver for RGB Glass. Currently used for selected PIC32MX device families.	RGB	mchpGfxLCC.c, mchpGfxLCC.h
Samsung S6D0129/S6D0139	8/16 bit PMP	drvTFT001.c, drvTFT001.h
LG LGDP4531	8/16 bit PMP	drvTFT001.c, drvTFT001.h
Renesas R61505U/R61580	8/16 bit PMP	drvTFT001.c, drvTFT001.h
Orise Technology SPDF5408	8/16 bit PMP	drvTFT001.c, drvTFT001.h
Epson S1D13517	8/16 bit PMP	S1D13517.c, S1D13517.h
Solomon Systech SSD1926	8/16 bit PMP	SSD1926.c, SSD1926.h
Solomon Systech SSD1289	8/16 bit PMP	drvTFT002.c, drvTFT002.h
Solomon Systech SSD1339 for OLED displays	8 bit PMP	SSD1339.c, SSD1339.h
Solomon Systech SSD1303 for OLED displays	8 bit PMP	SH1101A_SSD1303.c, SH1101A_SSD1303.h
Solomon Systech SSD1305 for OLED displays	8 bit PMP	SSD1305.c, SSD1305.h
Solomon Systech SSD2119	8/16 bit PMP	drvTFT002.c, drvTFT002.h
Sino Wealth SH1101A for OLED displays	8 bit PMP	SH1101A_SSD1303.c, SH1101A_SSD1303.h
Sitronix ST7529	8 bit PMP	ST7529.c, ST7529.h
Hitech Electronics HIT1270	8 bit PMP	HIT1270.c, HIT1270.h
Ilitek ILI9320	8/16 bit PMP	drvTFT001.c, drvTFT001.h
Himax HX8347	8/16 bit PMP	HX8347.c, HX8347.h
UltraChip UC1610	8 bit PMP	UC1610.c, UC1610.h



Microchip Graphics Library

Design Utilities

Graphics Resource Converter




- Converts graphical resources (images, fonts, binary files) into formats the Microchip Graphics Library can use
 - Bitmaps and fonts optimized for PIC[®] microcontrollers
 - JPEG encoding maintained
- Generate color palettes for use with Microchip Graphics Module

Graphical Display Designer



FREE




- WYSIWYG GUI Design utility with code generation
- Project Handling
- Stand alone or MPLAB® X IDE plug-in (Windows, Linux, Mac)

Third Party- VGDD

Visual Graphics Display Designer

http://virtualfab.it/mediawiki/index.php/VGDD:Visual_Graphis_Display_Designer

**HIGH FUNCTION
LOW COST**



- WYSIWYG GUI Design utility with code generation
 - Uses Microchip Graphics Library
- Project Generation using integrated MPLAB® X IDE Wizard
- Stand alone program (Windows only)


Visual Graphics Display Designer Features

- Provides visual screen creation
 - WYSIWYG results using Microchip Graphics Library
 - Integrated resource conversion for fonts and images
- Graphics system hardware configuration
 - Must use library supported LCD controller and display drivers
- C Code generation
 - Application templates with all callback functions
 - Required hardware set up and drivers included
- Editing features
 - Cut, copy and paste
 - Alignment guides
 - Snap to grid
 - Undo / Redo engine



Visual Graphics Display Designer Features

- **Generate MPLAB® X IDE project structure**
 - Application code template provided
 - All required library files populated into the project
 - Project properties set (heap allocation, memory optimizations, etc)
- **Import / Export screen files**
 - Allows reuse in multiple application
- **Customization support**
 - Design with your own colors
 - Select your own fonts and images
 - Support for user defined widgets
- **Widget event Handling**
 - Uses Microchip defined states and callback functions
 - Screen navigation using state machines
- **Screen simulation**
 - Player integrated with full version of VGDD
 - Visually see the GUI screen movement




Microchip Graphics Library

Basics



Terminology

- **Application Programming Interface (API):** A set of functions that can be called from an application to access features of another program or library.
- **Graphics Primitive:** An elementary graphics building block such as a point, line, arc, etc.
- **Graphics Object:** Any of the various shapes (e.g. buttons, charts, dials, etc) your program can render to the screen and control. These objects can be used to provide user input to your system.
- **Widget:** Another name for a graphics object.
- **Glyph:** A graphical representation, in a particular typeface, of all the individual symbols of any of the world's writing systems (e.g. alphabetic letters, Chinese characters, numerals, punctuation marks, etc.).



Microchip Graphics Library

Basics:
Images and Color




RGB Color Model

Definition

The RGB Color Model is an additive color model in which red, green, and blue light are added together in various ways to reproduce a broad array of colors. Colors are expressed as a triplet (RGB) Source: Wikipedia

- 16-bit
(65,536 colors)

- Red: 5 bits
- Green: 6 bits
- Blue: 5 bits
- RGB 565



- 18-bit
(262,144 colors)

- Red: 6 bits
- Green: 6 bits
- Blue: 6 bits
- RGB 666

- 24-bit
(1.678M colors)

- Red: 8 bits
- Green: 8 bits
- Blue: 8 bits
- RGB 888



Color Depth

Definition

Color Depth is the number of bits used to represent the color of a single pixel in an image or in a frame buffer. Color Depth is usually specified using a bpp (bits per pixel) notation. A higher color depth gives a broader range of distinct colors, but also requires more memory to store the image or frame.

- True Color => 24 bpp (16,777,216 colors)
- High Color => 16 bpp (65,536 colors)
- Indexed Color => Use of a color lookup table
 - Palette stored as part of image file
 - Required for images 8 bpp or less
- LCD System specifications – color depth refers to the capacity of the hardware
- Image Files – color depth impacts memory size



Frame Buffer Sizes

- PIC24 options up to 96KB RAM
- PIC32 options up to 128KB RAM
- Use external SRAM for frame buffers > 128KB

Display Resolution Typical Sizes			Color Depth/ Memory Requirement in (Bytes)				
			1 bpp (Mono)	2 bpp (4 shades)	4 bpp (16 shades)	8 bpp (256 colors)	16 bpp (65K colors)
WVGA	800x480	7"	48,000	96,000	192,000	384,000	768,000
VGA	640x480	5.7"	38,400	76,800	153,600	307,200	614,400
WQVGA	480x272	4.3"	16,320	32,640	65,280	130,560	261,120
QVGA	320x240	3.2"	9,600	19,200	38,400	76,800	153,600
Common for OLED	128x64	1"-2.7"	1,024	2,048	4,096	8,192	16,384

 Internal SRAM on
PIC24 DA or PIC32

 External SRAM

Color Lookup Table (Indexed Color)

- Converts the indexed color numbers stored in each pixel of frame buffer into physical colors
- Microchip's PIC24 DA family allows 256 entries of 16 bpp colors



65,536 colors



256 slots


Guess How Many Colors?



16 Shades – 4bpp
320x240 Resolution
37.5K byte per frame



256 Colors – 8bpp
320x240 Resolution
75K byte per frame



256 Colors – 8bpp
320x240 Resolution
75K byte per frame

PIC24F DA Color Lookup Table

- **Dynamic switching of different color palettes**
- **Each palette can utilize a different set of 256 colors**
- **Every screen update may have a different color palette, supporting different set of 256 colors**






Image Support


- Microchip Graphics Library supports both bitmap and jpeg formats
 - Color depth up to 24 bpp
- Images are converted using Graphics Resource Converter utility
 - May be compressed using run length encoding (RLE)
 - OR ... Fixed Huffman if PIC24xxxDAxxx's Inflate Processing Unit (IPU) is used

How are images used?


- Display company logos



- Create icons



- Provide user information (indicators)



How are images used?

- Create screen backgrounds



Design considerations

- Image size color depth impact memory use
- Example:

Image Size: 59x60 pixels
Color Depth: 32 bpp



Requires:
 $(59 \times 60 \times 32) / 8 = 14\text{K bytes}$

Image Size: 59x60 pixels
Color Depth: 16 bpp



Requires:
 $(59 \times 60 \times 16) / 8 = 7\text{K bytes}$

Design Considerations


- Image size and color depth impact memory requirements
- Guess how much memory needed for this screen?



- ANSWER: As drawn, this screen requires ~194,000 bytes

Graphics Resource Converter

Reduce Memory



Graphics Resource Converter version 3.3

File Project Help

Compression	Convert	Label	Type	Size (Bytes)	Description
None	<input checked="" type="checkbox"/>	Snowy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Sun_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Thunder_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Cloudy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Rainy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel

Dropdown menu options: None, RLE, IPU


■ Run Length Encoding (RLE)

- Software decompression
- May require more memory

C30 GFX Internal Flash 16 bpp

Graphics Resource Converter

Reduce Memory



Graphics Resource Converter version 3.3

File Project Help

Compression	Convert	Label	Type	Size (Bytes)	Description
None	<input checked="" type="checkbox"/>	Snowy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Sun_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Thunder_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Cloudy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>				

Compressed Size Difference

? Compressed size of the resource is larger than the uncompressed size.
Would you like to use the uncompressed resource?


Yes No

None
RLE
IPU

C30 GFX Internal Flash 16 bpp

Graphics Resource Converter

Reduce Memory



Graphics Resource Converter version 3.3

File Project Help

Compression	Convert	Label	Type	Size (Bytes)	Description
None	<input checked="" type="checkbox"/>	Snowy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Sun_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Thunder_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Cloudy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Rainy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel


None
RLE
IPU

- Inflate Processing Unit (IPU)
 - Hardware decompression
 - Uses Fixed Huffman encoding
 - Supported only in PIC24FJDA family

C30 GFX Internal Flash 16 bpp

Graphics Resource Converter

Reduce Memory



Graphics Resource Converter version 3.3

File Project Help

Compression	Convert	Label	Type	Size (Bytes)	Description
None	<input checked="" type="checkbox"/>	Snowy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
IPU	<input checked="" type="checkbox"/>	Sun_4bpp_32x32	Bitmap	440	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Thunder_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel
RLE	<input checked="" type="checkbox"/>	Cloudy_4bpp_32x32	Bitmap	487	32x32 pixels, 4-bits per pixel
None	<input checked="" type="checkbox"/>	Rainy_4bpp_32x32	Bitmap	550	32x32 pixels, 4-bits per pixel

testimages.xml C30 GFX Internal Flash 16 bpp


Compressed memory size

Graphics Resource Converter Project Settings



Either click toolbar icon OR...

Select from
Project menu




Graphics Resource Converter Project Settings

Choose compiler

Choose output format

Choose output
color depth



The screenshot shows the 'Graphics Resource Settings' dialog box. It has three main sections on the left: 'Compiler Type', 'Format Type', and 'Graphics Module Bits per Pixel'. Each section has a red box around the selected option, and a red arrow points from a text label to it. The 'Compiler Type' section has 'C30' selected. The 'Format Type' section has 'Internal Flash' selected. The 'Graphics Module Bits per Pixel' section has '16 bpp' selected. The 'OK' button is also highlighted with a red box. On the right side, there is a 'Description' area with text explaining the settings.

Graphics Resource Settings

Compiler Type

- C32
- C30

Graphics Module

Format Type

- Internal Flash
- External Flash
- Binary
- EDS EPMP

Graphics Module Bits per Pixel

- 16 bpp
- 24 bpp

Description

C30 - This is the setting for converting the resources into a format which MPLAB C30 is able to interpret. This setting is used for PIC24F, PIC24H and dsPIC devices.

Internal Flash - The resources are converted into a format which will be stored in the PIC device's internal Flash. This is a shared resource with program and psv memory.


16bpp - The bitmap image resources will be converted to support a 16bpp graphics model interface.

NOTE Bitmaps that are in 24bpp format will be converted to support the 16bpp interface.

OK Cancel


Graphics Resource Converter

Convert




Either click toolbar icon OR...

Select from
Project menu




Graphics Resource Converter

Convert





Using Images



Add generated files to the project



If using external memory, use the External Memory Programmer utility to program generated .hex file into the external memory



Gradients


- Smooth transition from one color to another
- Implemented in the primitive layer of the library
 - Vertical or horizontal are supported



Vertical Gradient Up



Vertical Gradient Down



Horizontal Gradient Left



Horizontal Gradient Right



Gradient Background

- Enhances HMI appearance
- Doesn't consume extra memory space



Microchip Graphics Library

Use Gradient

- In **GraphicsConfig.h**, enable gradients

```
#define USE_GRADIENT
```

- In application file(s) ...

- Call **BarGradient(...)** or **BevelGradient(...)**

```
...  
BarGradient( left, top, right, bottom,  
BRIGHTBLUE, BRIGHTRED, 100, GRAD_RIGHT );  
...
```






Gradients


'Length' Parameter

- Length describes where gradient will stop


```
...  
BarGradient( left, top, right, bottom,  
    BRIGHTBLUE, BRIGHTRED, length,  
    GRAD_RIGHT );  
...
```



length = 50



length = 75




length = 100



Transparency

- Used to “hide” colors
 - Hardware accelerated (if available)
 - OR use primitive layer APIs
- May be used to hide icon edges




Microchip Graphics Library Transparency Example

- Application requires ribbon icon over the screen background picture of a tree
- Problem: The ribbon icon is a bitmap with a black background that does not blend with the picture
- Solution: Use transparency to hide the icon's black background



Design Considerations

- Transparent colors are EXACT match
- Pixels of transparent color are ignored
- Example:
 - Transparent color set to white



- Use image processing tool (e.g. GIMP, Paint) to change corner color

Microchip Graphics Library Transparency Example

- In **GraphicsConfig.h**, enable transparency

```
#define USE_BITMAP_FLASH  
#define USE_TRANSPARENCY
```

- In **Main.c** ...

```
...  
extern const BITMAP_FLASH RibbonIcon;  
extern const BITMAP_FLASH ScreenBackground;  
...  
PutImage(0,0, (void *)&ScreenBackground);  
    TransparentColorEnable(BLACK);  
PutImage(0,0, (void *)&RibbonIcon);  
    TransparentColorDisable();  
...
```



Alpha Blending

- Layering effect where 2 images are blended
- Fading effect where a new image slowly appears as the old disappears
- Can be used to add an overlay to the HMI






Double Buffering

- **Two frames can be used for the GUI to ensure no renderring effect takes place to the user.**





Microchip Graphics Library

Basics: Fonts



Fonts

Definition:

Fonts are electronic data files containing a set of glyphs, characters and symbols. Fonts are created with font editors and are often considered works of art. Pre-created fonts are available from many sources, but may be licensed. Often times they are copyrighted. Please read all licensing agreements before use.

- **Use Graphics Resource Converter to convert fonts**
 - True Type (*.ttf)
 - Raster Fonts (*.fnt)
- **Resulting font ...**
 - Stored as an array in internal flash (const section)
 - or external memory
- **Unicode support via multi-byte characters**
 - AN1182 -- Fonts in the Microchip Graphics Library



How to get fonts

- Purchase fonts
 - Thousands of sources available online
 - Read license terms!
- Many websites offer “free” fonts
 - Look for open source fonts
(<http://www.openfontlibrary.org>)
 - Download Google Web Fonts
(<http://code.google.com/p/googlefontdirectory>)
- Create your own fonts using a font editor
 - Fony – freeware
 - FontForge – freeware
 - Other editors range in price
- Convert from Open Type
 - Results vary depending on the converter



Font Terminology

- **Body**

- Imaginary area that encompasses each glyph in a font

Font body impacts spacing
Font body impacts spacing
Font body impacts spacing
Font body impacts spacing

- **Point Size**

- The height of the glyph body


24 pt Arial
24 pt Calibri
24 pt Cochin
24 pt Gabriola



Font Terminology

- Anti-Aliasing

- Blurring the edges to soften the look
- Desirable for larger point sizes



- Style

- *Italics*, Bold, Anti-Aliased, etc

- Extended Glyphs

- Used render languages that use more than one byte to represent a single character

त + े = ते

Microchip Graphics Library Font Requirements


- Fonts must be converted
- Must have one font table per font type
 - EXAMPLE:
 - TimesNewRoman Bold 12 pts
 - TimesNewRoman Italic 12 pts
 - TimesNewRoman Bold 24 pts
 - => 3 font tables required
- May be stored in internal or external FLASH



Design Considerations

- Memory consumption factors:
 - Using multiple font types
 - Point size and weight of the characters
 - Number of characters in the font
 - Anti-aliased fonts consume ~2x the memory
 - Extended glyphs need at least 2 bytes per character
- Reduce font memory footprint by:
 - Minimize number of font types
 - Use Microchip Graphics Resource Converter to:
 - Filter the font (only store characters used)
 - Especially for extended glyphs
 - Reduce the font range (e.g. only store numbers)
 - Limit use of anti-aliased fonts

Graphics Resource Converter Fonts



Compression	Convert	Label	Type	Size (Bytes)	Description
None	<input checked="" type="checkbox"/>	Gentium_Bold_12	Font File	1,978	Heighth: 15 pixels, range: '' to '~'
None	<input checked="" type="checkbox"/>	Gentium_Italic_16	Font File	2,668	Heighth: 19 pixels, range: '' to '~'
None	<input checked="" type="checkbox"/>	Gentium_20	Font File	4,372	Heighth: 24 pixels, range: '' to '~'


Labels reflect:

- Font name
- Style
- Point size
- Reference name

Add all to calculate amount of memory required

Graphics Resource Converter

Reducing Font Memory




Convert only specific strings



Font Filtering

Application will use the string "Hello World!"

Since we only need 9 characters, how can we save flash memory space?




Font Filter Text File

- Editor must support unicode
 - Save in 16-bit unicode format
- Each line must have 3 sections:
 - `<String Label>:<String>//<comments>`
 - “//” Indicator required
 - Comments are optional
- Refer to the Graphics Resource Converter help file or to App Note 1182 for details

Graphics Resource Converter


Reducing Font Memory



Narrow the character range

Graphics Resource Converter

Reducing Font Memory



Graphics Resource Converter version 3.3


File Project Help

Compression	Convert	Label	Type	Size (Bytes)	Description
None	<input checked="" type="checkbox"/>	Gentium_Bold_12	Font File	1,590	Heigth: 15 pixels, range: '' to '~'
None	<input checked="" type="checkbox"/>	Gentium_Italic_17	Font File	2,280	Heigth: 19 pixels, range: '' to '~'
None	<input checked="" type="checkbox"/>	Gentium_20	Font File	3,984	Heigth: 24 pixels, range: '' to '~'
None	<input checked="" type="checkbox"/>	Gentium_20_1	Font File	528	Heigth: 24 pixels, range: '0' to '9'

Same font

~3.5 KB lower

C30 Internal Flash 16 bpp



Microchip Graphics Library

Basics: Widgets




Library Widgets

Picture

Meter

Buttons

Exit Scale ▲ ▼



Dial

Fri 10:11:13
Feb 15, 2008

Value

List box

Fri 10:14:44
Feb 15, 2008

Selection: Single Alignment: Center

- Home Appliances
- Home Automation
- Industrial Controls**
- Medical Devices
- Automotive

Listbox

Scrollbar (using Buttons and Slider)



Library Widgets

The image displays several user interface widgets from a library:

- Slider:** A horizontal bar with a rainbow color gradient, used for adjusting values. It is shown with three rows of controls: a red row with the value '255', a green row with '235', and a blue row with '000'. Each row has left and right arrow buttons.
- Group Box:** A container widget that organizes other widgets. It contains a 'Static Text' label, a 'Group Box' (nested), and three radio buttons labeled 'L', 'C', and 'R'. The 'C' radio button is selected.
- Edit Box:** A text input field containing the number '4807927200'. Below it is a numeric keypad with buttons for digits 1-9, *, 0, #, and a 'Hold' button. The '0' button is highlighted with a dashed border.
- Static Text:** A label widget displaying text, such as 'Microchip Graphics Library Static Text & Group Box Test.' and a timestamp 'Fri 10:20:21 Feb 15, 2008'.
- Radio Buttons:** Three circular buttons labeled 'L', 'C', and 'R' for selection.
- Button with Image:** A button featuring a red telephone handset icon.



Library Widgets


- Text Entry Widget
- Custom Widget creation described in AN1246

Enter ID Code			
1	2	3	del
4	5	6	spc
7	8	9	enter
*	0	#	

3659			
1	2	3	del
4	5	6	spc
7	8	9	enter
*	0	#	

Code accepted			
2	4	1	del
8	0	9	spc
3	7	5	enter
*	6	#	


Library Widgets



Analog Clock



Digital Meter




Grid

VGDD External Widgets


Require license for full version before they can be used



7 seg display



Super Gauge



Alarm Indicators



Widget Abbreviations

Obj =

Widget Name	Obj Abbreviation
Analog Clock	Ac
Button	Btn
Chart	Ch
Checkbox	Cb
Round Dial	Rdia
Digital Meter	Dm
Edit Box	Eb
Grid	Grid
Group Box	Gb
List Box	Lb
Meter	Mtr
Picture Control	Pict
Progress Bar	Pb
Radio Button	Rb
Slider/Scroll Bar	Sld
Static Text	St
Text Entry	Te
Window	Wnd



Creating Widgets

■ `ObjCreate(,,,)`

- Populates the widget structure
 - Adds widget to bottom of the active linked list
 - Returns a pointer to the widget structure
- ## ■ Heap required
- Widgets dynamically created
- ## ■ More details on using the linked list later...

ID_OBJ1

ID_OBJ2

ID_OBJ3

...

ID_OBJN

Creating Widgets

Object Header Members

- **ID**
 - Unique integer used to form a “Handle”
- **Location**
 - Top, left, bottom, right define placement
- **State**
 - 16-bit value that defines the widget state
- **Style Scheme pointer**
 - Structure that defines widget appearance



What is a “heap”?


Definition:

The heap is an unused pool of memory (similar to a stack) where a programmer may dynamically allocate memory using malloc() calls. In the embedded world, it is typically used to store recursive data structures (e.g. linked lists). Allocated memory must be freed by the application to avoid difficult runtime errors.

- **Proper memory management required**
 - **Memory Leak:**
 - Program does not free memory no longer needed
 - Leads to heap overrun
 - **Fragmentation:**
 - May occur when memory is deallocated in chunks
 - New malloc() requests may no longer fit
 - Clean up with a defrag engine (not provided in library)
 - Both result in runtime errors
- **GOLFree () – Graphics Library Function**
 - Removes entire linked list from heap

Creating Widgets Using VGDD

- VGDD Widget Property Window
- Used to create widget structure
- See changes as they are made




Widget

(Name)	Button1
(WidgetType)	Button
Bitmap	
Bottom	203
CDedType	ConstXcharArray
Focused	False
Hidden	False
HorizAlign	Center
Left	48
Locked	False
NoPanel	False
Pressed	False
Public	False
Radius	1
Right	127
Scheme	New
State	Enabled
Text	Button1
Top	125
TwoTone	False
VertAlign	Center
VGDDEvents	(Collection)
Zorder	1

(Name)
Indicates the name used in code to identify the object.



Widget Help



To find the ObjCreate APIs, expand the desired widget and select the appropriate create function.


..\Microchip\Help



Graphics Library Help.chm



Graphics Library Help.pdf



Microchip Graphics Library

Basics: Style Schemes



Widget Style Schemes

Definition:

The Style Scheme is a structure used by the library to define the appearance of widgets by assigning style properties.


- **Default scheme provided in `GOLCreateScheme.c`**
 - May be overridden by the application
 - Widgets without assigned schemes use the default scheme
- **`GOLCreateScheme ()` dynamically creates style schemes**
 - Populates a new scheme structure
 - Returns a pointer to that structure
- **Style Schemes may be created at compile time**
 - Use ‘&’ operator to reference scheme
- **All widgets use style scheme member values differently**
 - Help file provides pictures

Style Scheme Structure Defined in **GOL.h**

Type	Member	Description
GFX_COLOR	EmbossDkColor	3D dark color
GFX_COLOR	EmbossLtColor	3D light color
GFX_COLOR	TextColor0	Objects with text
GFX_COLOR	TextColor1	Objects with text
GFX_COLOR	Color0	Assigned to a state
GFX_COLOR	Color1	Assigned to a state
GFX_COLOR	ColorDisabled	Object in disabled state
GFX_COLOR	TextColorDisabled	Object in disabled state
GFX_COLOR	CommonBkColor	Used to hide objects
void	*pFont	Pointer to font selected
BYTE	AlphaValue	Define USE_ALPHABLEND
GFX_GRADIENT_SCHEME	gradientScheme	Define USE_GRADIENT

Creating Style Schemes Using VGDD

- VGDD Style Scheme Window
- Used to style schemes
- See how changes impact other widgets in the design



Schemes

New

Apply

A
Z
↓

New

Delete


(Name)	New
Color0	 169, 219, 239
Color1	 38, 199, 242
Colordisabled	 182, 210, 251
Commonbkcolor	 212, 237, 247
Embossdkcolor	 43, 85, 135
Embossltcolor	 212, 228, 247
GradientEndColor	 DarkGray
GradientLength	50
GradientStartColor	 LightGray
GradientType	GRAD_NONE
Referenced	False
Textcolor0	 7, 30, 72
Textcolor1	 255, 255, 255
Textcolordisabled	 245, 245, 220

(Name)
None for this Scheme



Style Scheme Help

- Library API
 - Graphics Library Configuration
 - Graphics Object Layer API
 - GOL Objects
 - GOL_OBJ_TYPE Enumeration
 - OBJ_HEADER Structure
 - DRAW_FUNC Type
 - FREE_FUNC Type
 - MSG_DEFAULT_FUNC Type
 - MSG_FUNC Type
 - Analog Clock
 - Button
 - Chart
 - Checkbox
 - Round Dial
 - Digital Meter
 - Edit Box
 - Grid
 - Group Box
 - List Box
 - Meter**
 - Picture Control
 - Progress Bar
 - Radio Button
 - Slider/Scroll Bar
 - Static Text
 - Text Entry
 - Window



Default Half Meter



Half Meter with Arc enabled



[Graphics Library Help.chm](#)




[Graphics Library Help.pdf](#)

[../Microchip/Help](#)

Creating Style Schemes Using VGDD

- VGDD Widget Info Window
- See widget style scheme information while designing
- Get resource information



The screenshot shows the 'Widget Info' window in a design tool. It has three tabs: 'Project Explorer', 'Output', and 'Widget Info'. The 'Widget Info' tab is active and displays the following information:

[Online Help on this Widget](#)

Instances:	2
-------------------	---

	Footprints in bytes
ROM:	2632
RAM:	20
Heap (x instance):	44

Style scheme information is shown for three widget parts:


- Button Face**
if (DISABLED)
Use **ColorDisabled**
Else
Use **Color0**
- Select Dot:**
if (DISABLED)
Use **TextColorDisabled**
else

Resource information is shown for three widget parts:

- RB HEAD
- RB 1
- RB 2



Style Scheme APIs



Descriptions for other APIs that affect the style scheme are found in the Graphics Library help file.


[../Microchip/Help](#)



[Graphics Library Help.chm](#)



[Graphics Library Help.pdf](#)



Microchip Graphics Library

Getting Started w/ VGDD

(Visual Graphics Display Designer)

Visual Graphics Display Designer

FOLLOW ALONG DEMO

VGDD - Visual Graphics Display Designer 3.6.4 - ACTIVATED

File Edit Tools Help

GOL Widgets

- <Pointer>
- StaticText
- Button
- EditBox
- CheckBox
- RadioButton
- Window
- GroupBox
- ListBox
- Picture
- ProgressBar
- RoundDial
- Slider
- Meter
- TextEntry

GPL Controls

- <Pointer>
- OutTextXY
- Arc
- Circle
- Line
- Rectangle

Custom Widgets

- <Pointer>
- Grid
- DigitalMeter
- AnalogClock

External Widgets

- <Pointer>
- Disp7Seg
- SuperGauge
- Alarm Indicator

New Project

Open existing Project

Open Demo Project ?

Recent Projects:

C:\MPLABXProjects\1667 GFX2\VGDD\backgrnd.vdp

Widget

Events

Schemes


Apply

New Delete

Project Explorer

Output

Show this page at next startup



Lab Exercise 1

Create a Splash Screen



Lab 1

Create a Splash Screen



Purpose

- In this exercise, you will demonstrate your ability to use the Microchip Graphics Library primitive layer functions to create a splash screen for our end application
- If time allows, you will explore the use of gradients and transparency to enhance the splash screen appearance



Lab Exercise 1

Create a Splash Screen



Objective

- Use the Graphics Resource Converter to generate font and image files for use in the application code
- Use primitive layer functions to render image and text strings to the display
- Explore how gradients and transparency can enhance the splash screen appearance


Low Cost Development Tools

PIC24FJ256DA210
Development Board

Graphics Display Truly 3.2
240x320 Board



OR



- PIC24FJ256DA210 Development Board (DM240312)
- Graphics Display Board (AC164127-x)
- MPLAB® ICD 3 In-Circuit Debugger (DV164035)
 - OR
- MPLAB REAL ICE™ In-Circuit Emulator (DV244005)



LCC and DA210

- **DA210:**
- **Built in graphics accelerator including: font rendering, CLUT, bitBLT, and accelerated bar draw functions.**
- **16 MIPS microcontroller.**
- **76k internal frame buffer**
- **Max pixel clock support VGA at 30Hz**
- **LCC:**
- **80 MIPS controller (this will get faster as the PIC32 portfolio grows)**
- **128k internal frame buffer. (this will get larger as the PIC32 portfolio grows)**
- **Pixel Clock Jitter in External Frame Buffer mode (will not be present on updated PICs)**
- **Max pixel clock support VGA at 20Hz**
- **Can be done in 8bit PMP mode (frees up IO pins).**




Lab 1

Create a Splash Screen



Procedure


- **Follow the instructions in the lab manual starting on page 1-1**



Lab Exercise 2

Create a Menu Screen

VGDD Style Schemes



- VGDD contains a style scheme manager
- Demo – Use the style scheme manager to alter style schemes

Lab 2

Create a Menu Screen



Purpose

- **In this exercise, you will demonstrate your ability to use the VGDD to create a menu screen for our end application**
- **You will enhance the icons through the use of transparency**


Lab 2

Create a Menu Screen



Objective

- Use VGDD to create a screen with:
 - 3 Rounded Buttons (one with text, two with image(no text))
 - 3 Static Texts to label the Buttons
- In VGDD, create and apply new style schemes
- Generate the code and program the microcontroller to examine the screen




Microchip Graphics Library

Interfacing the User:
GOL Messaging Interface



Message Interface




- **Simplifies integration of user input devices**
- **Allow application to efficiently manage widgets**
- **Provides seamless interface for the user**

Interfacing the User


Application Requirements Part 1

- **Detect user input**
 - Touchscreen driver files included in library
 - Sidebutton and keyboard detection up to user
- **Populate message structure (`GOL_MSG` type)**
 - Based on the input detected
- **Call `GOLMsg (&msg)`**
 - Where `&msg` is address of message structure
- **`GOLMsg (&msg)` translates the message**
 - Translation determines action (e.g. button looks pressed or not)
 - Application may customize widget response

VGDD Event Handling



- VGDD contains an event handler
- Allows customization of widget behavior
- But first, we need to learn a little more about widgets and events ...



Microchip Graphics Library

Interfacing the User:
Widget States



Widget States

- **16-bit value used to represent the widgets state**
 - Member of widget structure
- **Drawing states indicate widget needs to be:**
 - Fully drawn
 - Partially drawn
 - Hidden
- **Property states define action and appearance**
 - Button is pressed or released
 - Text alignment in a static text widget
- **Macros are used to identify state values**
 - Example: `BTN_DRAW` indicates button should be fully drawn
 - Logical OR used to combine states
 - Example: `BTN_DRAW | BTN_PRESSED` indicates button should be drawn in the pressed state



Button Drawing States

Statebit Macro	Description
BTN_DISABLED	Button will not accept messages
BTN_DRAW	Button must be fully redrawn
BTN_DRAW_FOCUS	Button focus must be redrawn
BTN_FOCUS	Button is focused
BTN_HIDE	Button must be covered with CommonBkColor
BTN_PRESSED	Button is in the pressed state
BTN_TEXTBOTTOM	Button text is bottom aligned
BTN_TEXTTOP	Button text is top aligned
BTN_TEXTLEFT	Button text is left aligned
BTN_TEXTRIGHT	Button text is right aligned
BTN_TOGGLE	Button will have a toggle behavior
BTN_TWOTONE	Button will be flat, with two colors
BTN_NOPANEL	Button will be created, but not drawn (icons)



Button Property States

Statebit Macro	Description
BTN_DISABLED	Button will not accept messages
BTN_DRAW	Button must be fully redrawn
BTN_DRAW_FOCUS	Button focus must be redrawn
BTN_FOCUS	Button is focused
BTN_HIDE	Button must be covered with CommonBkColor
BTN_PRESSED	Button is in the pressed state
BTN_TEXTBOTTOM	Button text is bottom aligned
BTN_TEXTTOP	Button text is top aligned
BTN_TEXTLEFT	Button text is left aligned
BTN_TEXTRIGHT	Button text is right aligned
BTN_TOGGLE	Button will have a toggle behavior
BTN_TWOTONE	Button will be flat, with two colors
BTN_NOPANEL	Button will be created, but not drawn (icons)







State Macros

- **SetState(pObj, state)**
 - Set specified state
 - States remain set until cleared
- **ClrState(pObj, state)**
 - Clear specified state
- **GetState(pObj, state)**
 - Get a widget's state
- **Where...**
 - **pObj** = pointer to the widget structure
 - **state** = desired state








State Bits Example Button Widget



```
if (GOL_DRAW())  
{  
    // Example Button text alignments  
    ClrState(pBtn, BTN_PRESSED);  
    SetState(pBtn, BTN_TEXTRIGHT);  
  
    // Example Button Focus  
    SetState(pBtn, BTN_FOCUSED);  
  
    // Example Button Action  
    SetState(pBtn, BTN_DISABLED);  
    state = BTN_PRESSED | BTN_TEXTTOP | BTN_TEXTLEFT;  
    SetState(pBtn, state);  
  
    // Example Hiding Button  
    SetState(pBtn, BTN_HIDE)  
}
```



Button States



```
if (GOL_DRAW())
{
// Example Button text alignments
ClrState(pBtn, BTN_PRESSED);
SetState(pBtn, BTN_TEXTRIGHT);




// Example Button Focus
SetState(pBtn, BTN_FOCUSED);

// Example Button Action
SetState(pBtn, BTN_DISABLED);
state = BTN_PRESSED | BTN_TEXTTOP | BTN_TEXTLEFT;
SetState(pBtn, state);

// Example Hiding Button
SetState(pBtn, BTN_HIDE)
}
```








Button States



```
if (GOL_DRAW())  
{  
    // Example Button text alignments  
    ClrState(pBtn, BTN_PRESSED);  
    SetState(pBtn, BTN_TEXTRIGHT);  
  
    // Example Button Focus  
    SetState(pBtn, BTN_FOCUSED);  
  
    // Example Button Action  
    SetState(pBtn, BTN_DISABLED);  
    state = BTN_PRESSED | BTN_TEXTTOP | BTN_TEXTLEFT;  
    SetState(pBtn, state);  
  
    // Example Hiding Button  
    SetState(pBtn, BTN_HIDE)  
}
```



Button States



```
if (GOL_DRAW())
{
// Example Button text alignments
ClrState(pBtn, BTN_PRESSED);
SetState(pBtn, BTN_TEXTRIGHT);






// Example Button Focus
SetState(pBtn, BTN_FOCUSED);

// Example Button Action
SetState(pBtn, BTN_DISABLED);
state = BTN_PRESSED | BTN_TEXTTOP | BTN_TEXTLEFT;
SetState(pBtn, state);

// Example Hiding Button
SetState(pBtn, BTN_HIDE)
}
```








Button States



```
if (GOL_DRAW())  
{  
    // Example Button text alignments  
    ClrState(pBtn, BTN_PRESSED);  
    SetState(pBtn, BTN_TEXTRIGHT);  
  
    // Example Button Focus  
    SetState(pBtn, BTN_FOCUSED);  
  
    // Example Button Action  
    SetState(pBtn, BTN_DISABLED);  
    state = BTN_PRESSED | BTN_TEXTTOP | BTN_TEXTLEFT;  
    SetState(pBtn, state);  
  
    // Example Hiding Button  
    SetState(pBtn, BTN_HIDE)  
}
```



Button States



```
if (GOL_DRAW())  
{  
    // Example Button text alignments  
    ClrState(pBtn, BTN_PRESSED);  
    SetState(pBtn, BTN_TEXTRIGHT);  
  
    // Example Button Focus  
    SetState(pBtn, BTN_FOCUSED);  
  
    // Example Button Action  
    SetState(pBtn, BTN_DISABLED);  
    state = BTN_PRESSED | BTN_TEXTTOP | BTN_TEXTLEFT;  
    SetState(pBtn, state);  
  
    // Example Hiding Button  
    SetState(pBtn, BTN_HIDE)  
}
```



Widget State Help

Every widget also has unique state bits. These can be found in the library help file as shown...


../Microchip/Help




Graphics Library Help.chm



Graphics Library Help.pdf





Microchip Graphics Library

Referencing Widgets



Pointer to Widget

Assign pointer when widget is created

```
void CreateButtons(void)
{
...
BUTTON          *pBtn
#define          ID_BTN2          16
...
...
pBtn =          BtnCreate(
                ID_BTN2,          // 2nd Button ID
                x3, y3,           // left, top
                x4, y4,           // right, bottom
                Radius,           // Rounded edges
                BTN_DRAW,         // Display button
                &arrow,           // use this bitmap
                NULL,             // no text
                altScheme);       // style scheme
...
}
```

Declare the Pointer

Assign Widget

Pointer to Widget Another Way...

- **GOLFFindObject (ID)**
 - Returns ADDRESS of the widget
 - Avoid mismatch warning by typecasting

```
BUTTON *pBtn ← Declare the Pointer
...
pBtn = (BUTTON*)GOLFFindObject (ID_BTN1);
SetState (pBtn, BTN_DRAW);
pBtn = (BUTTON*)GOLFFindObject (ID_BTN2);
SetState (pBtn, BTN_DRAW);
```

← Assign Widget



Widget Identifier


■ `GetObjID(*pObj)`

- Returns ID member of the widget structure

```
#define ID_BTN1  
BUTTON *pBtn;  
...  
currObjID = GetObjID(pBtn);  
switch(currObjID){  
    case ID_BTN1:  
        //do something useful  
        break;  
...}
```

Declare the Pointer

Assign Widget



Microchip Graphics Library

Interfacing the User:
Managing Widgets



Widget Abbreviations

Obj =

Widget Name	Obj Abbreviation
Analog Clock	Ac
Button	Btn
Chart	Ch
Checkbox	Cb
Round Dial	Rdia
Digital Meter	Dm
Edit Box	Eb
Grid	Grid
Group Box	Gb
List Box	Lb
Meter	Mtr
Picture Control	Pict
Progress Bar	Pb
Radio Button	Rb
Slider/Scroll Bar	Sld
Static Text	St
Text Entry	Te
Window	Wnd

Widget Management APIs

■ Widget's with text strings

- `ObjSetText(*pObj, *pText)`

- `ObjGetText(*pObj)`

 - Returns a pointer to the text string in use

- Works with button, checkbox, edit box, group box, radio button, static text, and window widgets

■ Widget's with images:

- `ObjSetBitmap(*pObj, *pImage)`

- `ObjGetBitmap(*pObj)`

 - Returns a pointer to the bitmap in use

- Works with picture and button widgets



Widget Management APIs

■ Positional Widgets

- `ObjSetPos(*pObj, posValue)`
- `ObjGetPos(*pObj)`
 - Returns the current position
- `ObjSetRange(*pObj, rangeValue)`
- `ObjGetRange(*pObj)`
 - Returns the current range
- Works with progress bar and slider widgets

■ Widgets have various management APIs available

■ Refer to library help file for more details



Widget Management API Help

- + Analog Clock
- + Button
- + Chart
- + Checkbox
- + Round Dial
- + Digital Meter
- + Edit Box
- + Grid
- + Group Box
- + List Box
- Meter
 - + Meter States
 - ? MtrCreate Function
 - ? MtrDraw Function
 - ? MtrSetVal Function
 - ? MtrGetVal Macro
 - ? MtrDecVal Macro
 - ? MtrIncVal Macro
 - ? MtrSetScaleColors Macro
 - ? MtrSetTitleFont Macro
 - ? MtrSetValueFont Macro
 - ? METER_TYPE Macro
 - ? MTR_ACCURACY Macro
 - ? MtrMsgDefault Function
 - ? MtrTranslateMsg Function
 - ? METER Structure

The widget management APIs are found under the individual widgets in the Graphics Object Layer section of the help file.


[../Microchip/Help](#)



[Graphics Library Help.chm](#)



[Graphics Library Help.pdf](#)




Microchip Graphics Library

Receiving Messages



Receiving Messages

Linked List



- **GOLMsg (&msg)**
 - User must supply pointer to a message structure
 - Immediately returns if **EVENT_INVALID**
 - Translates message
 - Finds affected widget in linked list
 - Modifies widget state
 - Returns TRUE when done



Message Structure

■ Message Structure

```
typedef struct {  
    BYTE        type;  
    BYTE        uiEvent;  
    SHORT       param1;  
    SHORT       param2;  
} GOL_MSG;
```

- `type`: identify input device type
- `uiEvent`: identify the event
- `param1`:
- `param2`: provide information based on `type` and `uiEvent`

Message Structure

type = TYPE_TOUCHSCREEN

- Valid **uiEvent** values
 - **EVENT_PRESS**
 - **EVENT_STILLPRESS**
 - **EVENT_RELEASE**
 - **EVENT_MOVE**
 - **EVENT_INVALID**
 - No touch
- **param1** = x coordinate of touch
- **param2** = y coordinate of touch



Message Structure

type = TYPE_KEYBOARD


- **param1** = Object identifier of receiving widget
- Valid **uiEvent** values
 - **EVENT_KEYSCAN**
 - **param2** = Scan Code
 - **EVENT_CHARCODE**
 - **param2** = character to add
 - **EVENT_INVALID**
 - No key pressed




AT keyboard scan codes are provided in the library help file

Widget Default Actions

Button




VGDD Event Handling




- VGDD contains a simulator
- Touchscreen driver included in project
 - Will need to change if using a side buttons
- Demo to show widget default events

Widget Management APIs VGDD Event Handler



Widget Management APIs

VGDD Event Handler



The screenshot shows the "Events Editor for Button1" dialog box. It features a table with columns for "Event", "Description", and "Code". The "Event" column has a checked checkbox for "BTN_MSG_PRESSED" with the description "Button pressed". Below the table, there are controls for "Event Code (check event to enable)", "Objects" (set to "Button1 (BUTTON) This Widget"), "Actions" (set to "Set Button Bitmap"), and "Bitmap" (with a dropdown menu showing "arrow1_4bpp_72x72" selected). There are "OK", "Cancel", and "Insert Code" buttons.

Event	Description	Code
<input checked="" type="checkbox"/> BTN_MSG_PRESSED	Button pressed	

Event Code (check event to enable)


Objects: Button1 (BUTTON) This Widget Actions: Set Button Bitmap **Insert Code**

Bitmap: **New**

OK **Cancel**

Widget Management APIs

VGDD Event Handler




Events Editor for Button1

Event	Description	Code
<input checked="" type="checkbox"/> BTN_MSG_PRESSED	Button pressed	

Event Code (check event to enable)

Objects: Actions:

```
BtnSetBitmap((BUTTON *)pObj, (void *)&bmparrow1_4bpp_72x72);  
RbSetCheck((RADIOBUTTON *)GOLFindObject(ID_Screen1_RadioButton1));
```



Microchip Graphics Library

Customizing widget events


`GOLMsgCallback()`



What is a Callback?


Definition:

A callback function allows a lower level software layer to call a subroutine defined in a higher layer.



GOLMsgCallback(, , ,)

- Called by `GOLMsg(&msg)`
- Only called if valid message is received





Interfacing the User

Application Requirements Part 1

- **Provide callback functions (REQUIRED)**
 - **GOLMsgCallback(, , ,)**
 - Called by **GOLMsg()** only if valid message received
 - Customize response to message event
 - **Example: Change button image on `EVENT_PRESS`**
 - **Example: Increase volume on `EVENT_STILLPRESS`**
 - **Example: Change screen state on `EVENT_PRESS`**
 - **GOLDDrawCallback()**
 - Called by **GOLDDraw()** when drawing is complete
 - Not dependent on message events
 - Customized drawing
 - **ONLY safe place to modify drawing properties**
 - **Example: Modify bars to form a signal strength meter**
 - Customized system response
 - **Example: Read a sensor and change a string**
 - **Example: Update a progress bar**




GOLMsgCallback(, , ,)

- Called by `GOLMsg(&msg)`
- **MUST** be provided in application code
- Perform custom actions:
 - Example: Change bitmap when button pressed
 - Example: Turn on LED when button pressed
- Input parameters:
 - `objMsg`: Translated message for the widget
 - `pObj`: Pointer to the widget
 - `pMsg`: Pointer to message structure
- Output:
 - `TRUE`: To perform default actions too
 - `'0'` : To skip default actions




GOLMsg () Flowchart




GOLMsgCallback(,,,)

Example



GOLMsgCallback(,,,)


Example



- Widget Actions:
 - Move slider thumb to the left
 - Add down arrow bitmap
- System Action:
 - Decrease motor speed


GOLMsgCallback(,,,)

Example




- Widget Actions:
- Move slider thumb to the right
 - Add up arrow bitmap
- System Action:
 - Increase motor speed

VGDD Event Handling



- Using VGDD event handler, code for the callback functions will be generated
- Event handler detects only one event at a time
- DEMO use of VGDD events



Lab Exercise 3

LED Control Screen



Lab 3

Interfacing the User



Purpose

- **In this exercise you will demonstrate your ability to use VGGD to generate code to handle widget events**
- **Additionally, you will demonstrate your ability to control the system by adding application code to the generated C files**



Lab 3

Interfacing the User



Objective

- **Manage widget events using VGDD to generate the code**
- **Explore how to use a checkbox to light an LED on the board**
- **Use status texts to inform the user of the current system status**



Lab 3

Interfacing the User



Procedure

- **Follow the instructions in the lab manual starting on page 3-1**



Lab 3


Interfacing the User

Results

The image displays two screenshots of a web-based interface titled "Development Board LED Control".

Left Screenshot: Shows a grid of ten LED controls. LED D3 is checked (green square), LED D5 is checked (green square), and LED D6 is unchecked (white square). The text "LED turned on" is displayed at the bottom. Callouts point to LED D3 (labeled "Check Box") and the "LED turned on" text (labeled "Static Text").

Right Screenshot: Shows a different state where LED D2 is unchecked (white square) and LED D4 is checked (green square). The text "LED turned on" is displayed at the bottom. Callouts point to LED D2 (labeled "Check Box") and the "LED turned on" text (labeled "Static Text").



Microchip Graphics Library


Customizing the Response

`GOLMsgCallback()`



Callback Reminder

- Called by `GOLDDraw()`
- Used to add system or widget response to user inputs





Interfacing the User

Application Requirements Part 2


- **Provide callback functions (REQUIRED)**
 - **GOLMsgCallback(, , ,)**
 - Called by GOLMsg() only if a valid event occurs
 - Customize response to message event
 - **Example: Change button image on EVENT_PRESS**
 - **Example: Increase volume on EVENT_STILLPRESS**
 - **Example: Change screen state on EVENT_PRESS**
 - **GOLDDrawCallback()**
 - Called by **GOLDDraw()** at end of drawing sequence
 - Not dependent on message events
 - Customized drawing
 - **ONLY safe place to modify drawing properties**
 - **Example: Modify bars to form a signal strength meter**
 - Customized system response
 - **Example: Read a sensor and change a string**
 - **Example: Update a progress bar**
 - Create new screen

Customized Drawing

GOLDDrawCallback ()

- Called by GOLDDraw ()
 - Drawing sequence is completed
- **MUST** be included in application code
 - Return **TRUE** to return control to GOLDDraw ()
 - Return '0' to keep drawing control
- Perform customized drawing
 - Example: Signal strength indicator
- Monitor and control for continuous events
 - Example: Read from a sensor and update screen
 - Example: Display a countdown timer
- Safest place to modify the linked list

Flowchart for GOLDDraw()




GOLDrawCallback()

Example: Battery Life Meter



Battery 100%



Battery 50%



Battery 80%




Battery Critical

- Read from power monitor circuit and update display accordingly



GOLDrawCallback()

Example – Flow Chart






Tips

GOLDrawCallback ()

- **To erase a bar**
 - Set the drawing color to the background color
 - Call `Bar ()` function with area for one or more bars
 - NOTE: `Bar ()` returns true when drawing is complete
- **To add a bar**
 - Set the drawing color to desired color
 - Call `Bar ()` with bar coordinates
- **No pointers are passed into `GOLDrawCallback ()`**
 - Use `GOLFindObject ()` to get the address of widget
- **Application must set drawing bits for widgets that need to be redrawn**
 - When updating widgets, make sure value changed before setting draw bit




Microchip Graphics Library

Putting it all together
Screen Management



Creating Widgets

Linked List



Recall...

- `ObjCreate(, , ,)`
 - Populates a structure for the widget
 - Adds widget to bottom of the linked list
- `GOLDDraw()`
 - Parses ACTIVE linked list
 - Redraws based on state bit settings



GUI Applications

Development Board Status

ROTATE POT CHECK TEMP LED CONTROL

Development Board LED Control

<input checked="" type="checkbox"/> LED D3	<input type="checkbox"/> LED D7
<input type="checkbox"/> LED D4	<input type="checkbox"/> LED D8
<input checked="" type="checkbox"/> LED D5	<input type="checkbox"/> LED D9
<input type="checkbox"/> LED D6	<input type="checkbox"/> LED D10

BACK

View Temperature

33
16
0
Te

View Potentiometer

500
333 666
166 833
0 812 1000
10K Potentiometer

BACK


Screen Management Options

Using Multiple Lists

- **Create Lists on the Fly**
- **Used by VGDD**
 - Use `GOLFree()` to delete active list
 - Frees heap library uses
 - Does not affect application heap
 - Use `ObjCreate(,,,)` to form new list
 - Minimize heap requirements
- **APIs in library to manage screens with multiple lists**




VGDD Event Handling



- Implements screen state machine
- Screen state changed in `GOLMsgCallback()`
- `GOLFree()` and `CreateScreen()` in `GOLDrawCallback()`



VGDD Screen States



DISPLAY SCREEN_x

- ⇒ GOLMsgCallback() functions
- ⇒ User event to change screens

CREATE SCREEN_x

- ⇒ GOLDrawCallback() functions
- ⇒ Erase old screen, create new screen

UPDATE SCREEN_x


- ⇒ GOLDrawCallback() functions
- ⇒ Primitive drawing



LCC

Interfacing to TFT LCD Panels

TFT LCD Panel: LCC Diagram



TFT LCD RGB Data Basics

- Raw color data sent to screen
- Different RGB Color formats
 - 332, 565, 666, 888
- Unused color tied to MSBs




LCD Timing Basics

- **Cycle (Display Period)**
 - Active Period + Blanking Period
- **Active Period**
 - This period displays the actual image
- **Blanking Period**
 - **Sync**
 - Used for synchronizing the display to graphics controller
 - **Front Porch**
 - Time between the end of the active time and the start of the sync pulse
 - **Back Porch**
 - Time between the end of a sync and the next active time



LCD Timing






MICROCHIP

*Regional Training
Centers*

PIC32 Peripherals Used for Graphics

Controllerless Solution: Diagram

- DMA is used to control LCD
- Most PIC32 with DMA and PMP can be used



Controllerless Solution: DMA Usage

- **Continuously reads/writes frame buffer data.**
- **DMA Transfer Interrupt (ISR) updates timing signals**

Controllerless Solution: PMP Usage

- **Read/Write Strobe acts as *Pixel Clock*.**
- **Data from DMA transmitted through PMP.**
- **Keeps system synchronized**





Controllerless Tasks

Controllerless Tasks: Frame Buffer

- **Frame containing the screen image must be stored somewhere**
 - **Internal – PIC32 SRAM**
 - **External – PSRAM on board**
- **DMA must read/write from this buffer**


Controllerless Tasks: Frame Rendering

- Usually refresh rates of 50-60 hz needed.
- Support of various resolutions




Controllerless Tasks: Update Pixels

- Helps to create dynamic interfaces
- Throughput varies depending on resolution
- PutPixel functionality






PutPixel: Internal



- The DMA shares the internal SRAM.
- Pixels are updated in conjunction with DMA. Pixel Updates wait for DMA read.



PutPixel: External





- There is only one PMP.
- DMA (Pixel Clock) suspended during pixel updates.
- Controlled to stabilize screen refresh



Lab 4 – LCC and Primitive Layer Demo

LCC (Low-Cost Controllerless) Graphics Board

Driving Graphics Displays without a Graphics Controller



Powered by any PIC32 Starter kit
 – 80MIPS 32-bit performance
 – 128KB of on-chip SRAM
 – High Speed 16-bit PMP
 – High Performance DMA keeps core loading to less than 5%!

On Board 512KB SRAM
 Can be "jumpered" in or out

Interfaces to Microchip Explorer 16


- Support for up to WQVGA @ 16bpp color
- PIC32 alone can drive QVGA @ 8bpp color

Interfaces to Microchip
 Display modules

PN: AC164144

LCC Graphics PICtail™: Internal Frame Buffer


- Supports 8bpp color on QVGA
- No external SRAM
- PIC32 SRAM used for frame buffer
- Color Look-up Table (CLUT)



256 colors available with 8bpp

LCC Graphics PICtail™: Color Look-up Table

- Applications have themed colors
- CLUT can be used for 16 BPP graphics.
- Color Palette stores color information



LCC Graphics PICtail™ External Frame Buffer

- Supports 16bpp color on QVGA
- External SRAM on LCC Graphics PICtail™ for frame buffer
- 13MHz pixel clock achieved



16bpp makes many colors available



Hands-on Lab 4



```
#define PMP_CONTROL (PMP_ON | PMP_MUX_OFF | PMP_READ_WRITE_EN|PMP_CS2_EN | PMP_CS2_POL_LO | PMP_WRITE_POL_LO | PCLK_POLARITY)  
#define PMP_MODE (PMP_DATA_LENGTH | PMP_MODE_MASTER2 |PMP_WAIT_BEG_1 | PMP_WAIT_MID_1 | PMP_WAIT_END_1)
```

void ResetDevice(void)

```
{  
  
    // setup the PMP  
    mPMPOpen(PMP_CONTROL, PMP_MODE, PMP_ADDRESS_LINES, PMP_INT_ON);  
    PMADDR = 0x0000;  
  
    // Open the desired DMA channel  
    DmaChnOpen(1, 0, DMA_OPEN_DEFAULT);  
  
    // set the transfer event control: what event is to start the DMA transfer  
    DmaChnSetEventControl(1, DMA_EV_START_IRQ( TIMER_2_IRQ));  
  
    // set the transfer parameters: source & destination address, source & destination size, number of bytes per event  
    DmaChnSetTxfer(1, &GraphicsFrame[0], (void*)&PMDIN, HBackPorch, 1, 2);  
  
    INTSetVectorPriority(INT_VECTOR_DMA(1), INT_PRIORITY_LEVEL_7);  
    INTSetVectorSubPriority(INT_VECTOR_DMA(1), INT_SUB_PRIORITY_LEVEL_3);  
                                                                    // set INT controller priority  
                                                                    // set INT controller sub-priority  
  
    DmaChnSetEvEnableFlags(1, DMA_EV_BLOCK_DONE);  
    INTEnable(INT_SOURCE_DMA(1), INT_ENABLED);  
                                                                    // enable the transfer done interrupt, when all buffer transferred  
                                                                    // enable the chn interrupt in the INT controller  
  
    DCH1CONbits.CHPRI = 0b11; //DMA channel has highest priority  
  
    // once we configured the DMA channel we can enable it  
    DmaChnEnable(1);  
  
    OpenTimer2(T2_ON | T2_SOURCE_INT | T2_PS_1_1, 27);  
                                                                    //Start Timer  
}
```



```
void __ISR(_DMA1_VECTOR, ipl7) DmaHandler1(void)
```

```
{  
    static BYTE GraphicsState = 1;  
    static short line =0;  
  
    if(GraphicsState ==1)  
    {  
        DCH1SSIZ = LINE_LENGTH;  
        GraphicsState++;  
  
        if(line++ >= -1)  
        {  
            VSYNC =1;  
            DATA_ENABLE =1;  
  
            DCH1SSA = _VirtToPhys(&GraphicsFrame[line][0]);  
  
            if(line == (FRAME_HEIGHT))  
            {  
                VSYNC =0;  
                line= -VER_BLANK;  
            }  
        }  
    }  
    else  
    {  
        HSYNC =0;  
        DATA_ENABLE =0;  
  
        //Perform Back Porch Clock Signal  
        PMDINSET=1;  
  
        HSYNC = 1;  
        DCH1SSIZ = HBackPorch;  
        GraphicsState= 1;  
    }  
  
    DCH1INTCLR = 0x08;      //CHBCIF = 0  
    IFS1CLR = 0x20000;    //DMA1IF =0  
    DCH1CONSET =0x80;    //CHEN =1  
}
```

DMA ISR



Putpixel

```
void PutPixel(short x, short y)
{
    if(_clipRgn)
    {
        if(x < _clipLeft)
            return;
        if(x > _clipRight)
            return;
        if(y < _clipTop)
            return;
        if(y > _clipBottom)
            return;
    }

    GraphicsFrame[(GetX()-x)][y] = _color;
}
```

Lab Exercise 4



Purpose

Understand how to send data to an LCD display. After this lab the student should be able to send color data to an LCD Panel and see the data on the screen.




Procedure

Follow the directions in the lab manual starting on page 1-1


Objectives:

- Use the LCC Graphics board to run the primitive layer demo
- Use microchip graphic library to make changes to the demo

Lab Exercise 4




Expected Results –





Lab 4 Summary

- **TFT LCD panels can be driven with only a PIC32**
- **Accomplished using DMA and PMP peripherals**
- **LCC graphics board available for development**



Summary

Steps for design with Microchip Graphics Objects Library

- Use a GUI design tool to design screens, import necessary fonts and image files, and establish style schemes
- Configure hardware using **HardwareProfile.h**
- Configure Graphics Objects Layer using **GraphicsConfig.h**
- Place appropriate files in project
- Write application code
 - Use typedefs (see next slide)
 - Implement message structure
 - Remember, allow GOLDraw() to finish parsing linked list before processing messages
 - Add callback functions to customize application response and manage GUI screen states
- Compile, build and run!



Microchip Graphics Library Types

Type	Description
<code>XCHAR</code>	Sets type of character used in library. Types are <code>char</code> , <code>unsigned char</code> , or <code>short</code> depending on setting in <code>GraphicsConfig.h</code>
<code>GFX_COLOR</code>	Sets type of color used in library. Types are <code>BYTE</code> , <code>WORD</code> or <code>DWORD</code> based on <code>COLOR_DEPTH</code> setting in <code>GraphicsConfig.h</code>
<code>FONT_FLASH</code>	Refers to fonts stored in internal FLASH
<code>FONT_EXTERNAL</code>	Refers to fonts stored in external memory
<code>IMAGE_FLASH</code>	Refers to images stored in internal FLASH
<code>IMAGE_EXTERNAL</code>	Refers to images stored in external memory
<code>GOL_SCHEME</code>	Refers to style scheme structures used by widgets
<code>GOL_MSG</code>	Refers to the message structure used in the library's messaging interface
<code>OBJ_HEADER</code>	Refers to the first member of all widget structures. Specifies ID, location (and dimensions), states and style scheme to be used by widget
<code>WIDGET</code>	Refers to the <i>widget</i> structures. See library help for complete listing



Words of Wisdom

- **Avoid heap fragmentation**
 - Use `GOLFree()`
 - Do NOT ...
 - Manually remove widgets from active list
 - Do NOT...
 - Modify list until `GOLDDraw()` is complete
- **Avoid weird drawing effects**
 - Do NOT ...
 - Modify drawing properties until `GOLDDraw()` has completed the drawing sequence
- **Watch the list pointers**

Microchip Graphics Library

Static Memory Use


- **Define and initialize widget structures**
- **Define and initialize style scheme structures**
- **Must maintain linked list**
- **All other concepts remain**



MICROCHIP

Regional Training
Centers

Microchip Graphics Library Help



Today's class was taught using v3.04.02 of the Microchip Graphics Library. If you have been using older versions, please refer to the migration notes in the Release Notes section. Much has changed!

..\Microchip\Help



Graphics Library Help.chm



Graphics Library Help.pdf



Summary

Today you learned how to:

- **Write programs to display images, fonts, and primitives on LCD panel**
- **Write programs to display and control widgets on LCD panel**
- **Graphically create application code to fully utilize Microchip Graphics Library**



Graphics Design Center

<http://www.microchip.com/graphics>

MICROCHIP myMicrochip Login English 中文 日本語

Home Products Design Support Applications Buy/Sample Corporate What's New

search

Graphics Displays

Overview Technology **Products** Support Getting Started

NEWS AND EVENTS PIC24FJ DA Family Integrated Graphics

ADDING GRA... ASIER

Find Microchip Controllers for Graphics Applications


FREE MICROCHIP GRAPHICS LIBRARY

FREE MICROCHIP GRAPHICS LIBRARY

Forecast 82° High: 85° Low: 77° 03.12.10 10:00 PM 75° 80° 40% Humidity 76°

Graphics Design Center

<http://www.microchip.com/graphics>



myMicrochip Login English 中文 日本語

search

Home Products Design Support Applications Buy/Sample Corporate What's New

Resources and Support

Related Pages

Featured Videos

Find Products

MICROCHIP

Graphics Displays

Overview Technology Products Support Getting Started

NEWS AND EVENTS PIC24FJ DA Family with Integrated Graphics

ADDING GRAPHICS TO YOUR APPLICATIONS

EXPLORE THE

FREE MICROCHIP GRAPHICS LIBRARY

FREE MICROCHIP GRAPHICS LIBRARY

Forecast 82° High: 85° Low: 77° Partly Cloudy 03.12.10 10:00 PM 75° 80° 40% Humidity 76°

App Notes, Webinars, Forums and Training



MICROCHIP

Regional Training
Centers

Graphics Design Center

<http://www.microchip.com/graphics>

myMicrochip Login English 中文 日本語

search

Home Products Design Support Applications Buy/Sample Corporate What's New

Resources and Support

Related Pages

Featured Videos

Find Products

Graphics Displays

Overview Technology Products Support Getting Started

NEWS AND EVENTS PIC24FJ DA Family with Integrated Graphics

ADDING GRAPHICS TO YOUR APPLICATION

EXPLORE THE POSSIBILITIES

FREE MICROCHIP GRAPHICS LIBRARY

Development Boards
Download Microchip
Applications Library



Tools

- **Microchip Graphics Library v3.04.02**
 - <http://www.microchip.com/mla>
- **MPLAB[®] X IDE**
 - <http://www.microchip.com/mplabx>
- **MPLAB 16- and 32-bit Compilers**
 - <http://www.microchip.com/mplabc>
- **VGDD**
 - <http://virtualfab.it/mediawiki/index.php>
VGDD:Visual_Graphis_Display_Designer



MICROCHIP

**Regional Training
Centers**

Tools



- **Explorer 16 Development Board (DM240001)**
- **PIC24FJ256DA210 Development Board (DM240312)**
- **Multimedia Expansion Board (MEB) (DM320005)**
- **PIC32 Starter Kits (DM320001, DM320003-2, DM320004*)**

Note: * DM320004 (PIC32 Ethernet Starter Kit) is only compatible with MEB



Tools



- **MPLAB[®] Starter Kit for PIC24F (DM240011)**



- **MPLAB Starter Kit for PIC24H (DM240021)**




- **Graphics Display Board with 3.2" Display Kit (AC164127-3)**



- **PIC24FJ256DA210 Development Kit (DV164039)**




Tools



- **Graphics LCD Controller
PICtail™ Plus SSD1926 Board
(AC164127-5)**
- **Graphics Display Truly 3.2”
240x320 Board (AC164127-4)**
- **Graphics Display Powertip 4.3”
480x270 Board (AC164127-6)**
- **Graphics Display Prototype
Board (AC164139)**

High Resolution Displays

Truly 7" WVGA (800x480)



- Resistive 4-wire touch screen
 - AR1020 Touch Controller
- Works with Epson S1D13517 Board

Part Number:
AC164127-9


Truly 5.7" VGA (640x480)



- Resistive 4-wire touch screen
 - AR1020 Touch Controller
- Works with Epson S1D13517 Board and others

Part Number:
AC164127-8

Graphics Epson S1D13517 Board



The Graphics Controller PICtail™ Plus Epson S1D13517 Board allows evaluating Microchip Technology's solution and graphics library for 16- and 32-bit microcontrollers. The Epson S1D13517 offers hardware acceleration for alpha-blending, transparency, animation, multiple buffering, and picture in picture. The kit is compatible with the Explorer 16 development board (DM240001) or one of the PIC32 Starter Boards (DM320001, DM320003).

The features include:


- Graphics display controller Epson S1D13517 supporting 18-bit HR-TFT, and 9/12/18/24 bit TFT interface
- PIC32 Starter Kit Connector
- 16 Megabit (2Mx8) serial flash memory for additional data storage
- Display connector for interfacing with different display boards
- PICtail Plus Interface for connecting to Explorer 16 Development Board
- PIC32 Starter Kit Connector



MICROCHIP

**Regional Training
Centers**

Suggested Reading




Programming 16-bit Microcontrollers in C by Lucio Di Jasio

ISBN-10: 0750682922

ISBN-13: 978-0750682923


<http://www.flyingpic24.com>



Programming 32-bit Microcontrollers in C by Lucio Di Jasio

ISBN-10: 0750687096

ISBN-13: 978-0750687096



Thank You!



MICROCHIP

*Regional Training
Centers*

Trademarks

The Microchip name and logo, the Microchip logo, dsPIC, KeeLoq, KeeLoq logo, MPLAB, PIC, PICmicro, PICSTART, PIC³² logo, rfPIC and UNI/O are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

FilterLab, Hampshire, HI-TECH C, Linear Active Thermistor, MXDEV, MXLAB, SEEVAL and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Analog-for-the-Digital Age, Application Maestro, chipKIT, chipKIT logo, CodeGuard, dsPICDEM, dsPICDEM.net, dsPICworks, dsSPEAK, ECAN, ECONOMONITOR, FanSense, HI-TIDE, In-Circuit Serial Programming, ICSP, Mindi, MiWi, MPASM, MPLAB Certified logo, MPLIB, MPLINK, mTouch, Omniscient Code Generation, PICC, PICC-18, PICDEM, PICDEM.net, PICKit, PICtail, REAL ICE, rfLAB, Select Mode, Total Endurance, TSHARC, UniWinDriver, WiperLock and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.
All other trademarks mentioned herein are property of their respective companies.

© 2012, Microchip Technology Incorporated, All Rights Reserved.